

**DIGITUS Plug&View OptiZoom Pro**

DN-16048 4016032356950



**DIGITUS Plug&View OptiZoom Pro**  
**2MP H.264 IP 11N Day&Night Outdoor PTZ camera 12V, 2GB TF, IR**

**Your wireless Plug&View IP camera with pan and tilt fuction, IP66 housing and optical zoom**

The Plug & View OptiZoom Pro secures your outdoor area. Whether placed in the garage yard, garden or in the driveway, the OptiZoom Pro is very robust and the largest model of the current Plug & View camera series. The camera is in a safe and stable housing, thanks to the IP66 protection class. Thus it is splash-proof. The lens offers a viewing angle of 30.8 to 95.9 degrees. Equipped with a resolution of 2 megapixels, the OptiZoom Pro provides excellent surveillance images, which you can access, of course, through the browser or app on your smartphone or tablet. Six IR LEDs provide good visibility even in the dark, the range here is 30 meters. The 4times optical zoom helps you to optimally adjust your camera to the monitored area. The power can also be provided with high POE. Thus, the camera can also be operated without additional power supply. This camera model is ideal for homeowners or small businesses that want to have their own property in view. The installation is done, as with all Plug & View models in three easy steps. Everything works easily with Plug & View.



- 1 2 megapixel video resolution (Full HD 1920 x 1080, HD720 1280 x 720)
- 1 Low-latency video streaming with H.264 compression format
- 1 Powerful mobile surveillance supporting iOS and Android devices
- 1 Wireless LAN according to the newest 11n standard for fluent image transmission
- 1 IK10 vandal-proof protection
- 1 IP66 housing design for outdoor use
- 1 Suitable for the most common browsers
- 1 Simple and fast installation with P2P support & QR-code-scanning
- 1 IR-LEDs and IR cut filter included for day & night surveillance
- 1 Pan and tilt camera controllable by different network devices
- 1 LAN speed: 10/100Base-TX Ethernet
- 1 Supports up to 25fps video frame rate at HD720 and 15fps at Full HD
- 1 Integrated 2 GB storage for recording videos and snapshots
- 1 Advanced motion detection, record and save events via e-mail/FTP/Google Drive
- 1 Operating temperature: -10 °C ~+50 °C
- 1 Power source (±10 %): DC12 V / 2 A
- 1 High PoE - High Power over Ethernet (PoE+)
- 1 Dimensions (mm): 235 (L) x 190 (W) x 140 (H)
- 1 Supports DIGITUS® Plug&View app for smartphone and tablet access
- 1 4 times optical zoom, adjustable via DIGITUS® Plug&View app or under mydigitus.net
- 1 Optical zoom lens: F1.4 / 2.8-12 mm
- 1 Adjustable horizontal viewing angle: 30.8°- 95.5°
- 1 WPS (Wireless Protected Setup) function provides fast, easy, and secure wireless encryption
- 1 Minimum system requirement Internet: DSL 1000 (1.024kBit download / 384kBit upload)
- 1 Minimum system requirement smartphone access: 3G network connection

**Package Content**

- 1 IP camera
- 1 Patch cable
- 1 Mounting kit
- 1 Product support CD-ROM
- 1 Power supply

## DIGITUS Plug&View OptiZoom Pro

DN-16048 4016032356950

### → Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	8	10,60	46,00	38,00	35,00	61180,00
Packaging Unit Inside	1	1,33	23,50	26,00	16,50	10081,50
Packaging Unit Single	1	1,33	23,50	26,00	16,50	10081,50
Net single without Packaging	1	0,00	0,00	0,00	0,00	0,00

### → Operating systems



### → Packaging type

