



IP Telephony

Delivering Your Voice in Real Time



Contents

High Definition Color PoE IP Phones	2
SIP IP Intercoms	3
HD Touch Screen Conferencing Phone	4
Home Automation Control Pad	4
Color LCD IP Phone with Expansion Module	5
Enterprise IP Phone with Expansion Module	6
High Definition IP Phones	7
Internet Telephony PBX System	9
Voice Gateways	11
Analog Telephony Adapters	12
SIP IP Camera	12
SIP Public Announcement Adapter with PoE	13
Voice Router	14
Multipoint Control Unit	14
Unified Office Gateway	14

Flexible and Cost-Effective SIP Communications Solutions



Beneficial Products



Color Phone with
Color Expansion Module



SIP IP Door Phone



SIP Camera



All-capacity IP PBX

High Definition Color PoE IP Phones

IP Phones			
Model	VIP-1120PT	VIP-2140PT	

Product Image



	Ethernet Port(RJ45)	1 WAN + 1 LAN	1 WAN + 1 LAN
Hardware	PoE	●	●
	Gigabit	-	●
	HD Audio	●	●
	Line Keys	2	-
	Soft Keys	4	4
	DSS Keys	-	6
	LCD Display	2.4" TFT-LCD	2.8"+2.4" TFT-LCD
Voice Features	SIP Account	2	4
	FoIP	-	-
	Voice Codec	G.711, G.722, G.723, G.726, G.729	G.711, G.722, G.723, G.726, G.729
Telephone Features	Video Codec	-	-
	3-way Conferencing	●	●
	Caller ID	●	●
	Call Mute/Holding	●	●
	Call Waiting	●	●
	Call Forward/Transfer	●	●
	Call History	●	●
	Do Not Disturb (DND)	●	●
	Hotline/Speed Dial	●	●
	Phonebook	●	●
	Message Waiting Indicator (MWI)	●	●
	Auto-Provisioning	●	●
	TR-069	●	●
	QoS	●	●
	Web call	●	●
	BLF	-	●
	Auto Answer (Intercom)	●	●
	Recording	-	-
	Media Player	-	-
	Ext. Console	-	-
	Photo Frame	●	●
	VPN (PPTP/L2TP)	L2TP, Open VPN	L2TP, Open VPN
	802.1Q VLAN	●	●

High Definition Color PoE IP Phone



SIP IP Intercoms

SIP IP Door Phone				
Model		HDP-1100PT	HDP-5240PT	HDP-5260PT
Product Image		 		
Hardware	Sensor	1/4" 1 mega-pixel CMOS sensor	1/4" 1 mega-pixel CMOS sensor	1280 x 760, CMOS sensor
	Viewing Angle	H: 113°	H : 110° / V : 95°	H : 60° / V : 40°
	Monitoring Range	3 meters	-	5 meters
	LED	White LED x 6, effective up to 1 meter	-	IR LED x 3, effective up to 2 meters
	PoE	●	●	●
	Ethernet	10/100BASE-T RJ45 Ethernet interface	10/100BASE-T RJ45 Ethernet interface	10/100/1000BASE-T RJ45 Ethernet interface
	I/O Port	DI x 2, DO x 2, DC out 12V x 1	DI x 1, DO x 1, DC out 12V x 1	DI x 1, DO x 1, DC out 12V x 1
	Housing	-	IP65	IP66/IK10
	Installation	Wall-mount type	Wall-mount type	Wall-mount type In-wall mount (optional)
Video & Audio	Max Resolution	720p (1280 x 720 @ 20fps)	720p (1280 x 720 @ 20fps)	720p (1280 x 760 @ 30fps)
	Video Compression	H.264, M-JPEG	H.264	H.264 / H.263
	Audio Streaming	Two-way audio	Two-way audio	Two-way audio
	Audio Compression	RTSP: G.711, AAC	G.711a/u, G.723.1, G.726-32K, G.729AB	G.711a/u, G.723.1, G.726-32K, G.729AB, iLBC, AMR
	Microphone	●	●	●
	Speaker	●	●	●
	Acoustic Echo Cancellation	●	●	●
Door Phone Features	Protocol	SIP 2.0 (RFC 3261)	SIP 2.0 (RFC 3261)	SIP 2.0 (RFC 3261)
	SIP Intercom	●	●	●
	Door Lock Control	●	●	●
	RFID	-	●	●
	Manual Alarm	●	●	●
	Remote Monitoring	●	●	●
	App	● (Cloud Bell)	3rd Party SIP Softphone	3rd Party SIP Softphone

Enjoy a Intelligent and user-friendly Lifestyle



Camera Monitoring
Z-wave Control
Control Pad
Doorphone Intercom

Touch Screen SIP Controller HTS-1000P



HDP-5260PT
Multi-unit Apartment Vandalproof SIP Door Phone with RFID and PoE

HDP-5240PT
Multi-unit SIP Door Phone with RFID And PoE

HDP-1100PT
SIP Door Phone with PoE

Cloud Bell App for Door Phone

App Store
Google play

Touch Screen Conferencing Phone

Home Automation

IP Phone	
Model	ICF-1800

Product Image



Hardware	Ethernet Port (RJ45)	1 WAN + 1 LAN
	PoE	●
	Gigabit	●
	HD Audio	●
	USB	●
	Audio/Video Output	HDMI
Voice Features	LCD Display	7" TFT LCD, 800x480 pixels
	SIP Account	6
	FoIP	-
	Voice Codec	G.711, G.723, G.729a/b
Telephone Features	Video Codec	H.263, H.264
	3-way Conferencing	●
	Caller ID	●
	Call Mute/Holding	●
	Call Waiting	●
	Call Forward/Transfer	●
	Call History	●
	Do Not Disturb (DND)	●
	Hotline/Speed Dial	●
	Phonebook	●
	Message Waiting Indicator (MWI)	●
	Auto-Provisioning	●
	TR-069	●
	QoS	●
	Web Call	●
	BLF	●
	Auto Answer (Intercom)	●
	Recording	●
	Media Player	●
	Ext. Console	-
	Photo Frame	●
	VPN (PPTP/L2TP)	●
	802.1Q VLAN	●

Control Pad	
Model	HTS-1000P

Product Image



Hardware	Screen Size	10.1 inch
	Brightness	250 cd/m2
	Video Resolution	1024 x 600
	Aspect Ratio	16:9
	Touch Panel	Projected capacitive (multi touch)
	PoE	●
Installation	Installation	VESA-mount type
	Ethernet	IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX
	Wireless	IEEE 802.11b/g/n
	Encryption Security	WEP (64/128-bit) WPA-PSK (TKIP)/ WPA2-PSK (AES) WPA (TKIP)/WPA2 (AES)
Video / Audio	Video Code	H.264
	Audio Streaming	Two-way audio
	Microphone	●
	Speaker	●
Features of Home Automation Products	Acoustic Echo Cancellation	●
	SIP Intercom	●
	Weather Report	●
	Janitor	●
	Door Lock for Door Phone	●
	Door Lock for Z-Wave Device	●*
	Cameras	●
	Contacts	●
	Z-Wave Control	●*

* Controlled with PLANET HAC-1000 system devices.

Make Your Home Smart and Safe



Color LCD IP Phone with Expansion Module

IP Phone		
Model	VIP-6040PT	VIP-EXT-40

Product Image



Color Icon

Hardware	Ethernet Port (RJ45)	1 WAN + 1 LAN (Gigabit)
	PoE	●
	Gigabit	●
	HD Audio	●
	Line Keys	4
	Soft Keys	4
	DSS Keys	10
	LCD Display	3.5" TFT-LCD, 480 x 320 pixels
Voice Features	SIP Account	4
	FoIP	-
	Voice Codec	G.711, G.722, G.723, G.726, G.729
	Video Codec	-
Telephone Features	Conferencing	5-way
	Caller ID	Caller ID Photo
	Call Mute/Hold	●
	Call Waiting	●
	Call Forward/Transfer	●
	Call History	●
	Do Not Disturb (DND)	●
	Hotline/Speed Dial	●
	Phonebook	●
	Message Waiting Indicator (MWI)	●
	Auto-Provisioning	●
	TR-069	●
	QoS	●
	Web Call	-
	BLF	●
	Auto Answer (Intercom)	●
	Recording	-
	Media Player	-
	Ext. Console	VIP-EXT-40

HD Voice and Color Screen

Make Your Communication Wonderful!



HD Voice

Gigabit

Photo Caller ID

▶ VIP-6040PT + VIP-EXT-40

Enterprise IP Phone with Expansion Module

IP Phones		
Model	VIP-5060PT	VIP-EXT-26

Product Image



Hardware	Ethernet Port (RJ45)	1 WAN + 1 LAN (Gigabit)
	PoE	•
	Gigabit	•
	HD Audio	•
	Line Keys	4
	Soft Keys	4
	DSS Keys	8
	LCD Display	128 x 64 Graphic
Voice Features	SIP Account	6
	VoIP	-
	Voice Codec	G.711, G.722, G.723, G.726, G.729
	Video Codec	-
Telephone Features	3-way Conferencing	•
	Caller ID	•
	Call Mute/Hold	•
	Call Waiting	•
	Call Forward/Transfer	•
	Call History	•
	Do Not Disturb (DND)	•
	Hotline/Speed Dial	•
	Phonebook	•
	Message Waiting Indicator (MWI)	•
	Auto-Provisioning	•
	TR-069	•
	QoS	•
	Web Call	•
	BLF	•
	Auto Answer (Intercom)	•
	Recording	-
	Media Player	-
	Ext. Console	VIP-EXT-26

Gigabit HD Voice PoE IP Phone
with Extension Console



▶ VIP-5060PT + VIP-EXT-26



Supports **5** extension consoles
max. **130** definable keys

High Definition IP Phones

IP Phones					
Model	VIP-1000T	VIP-1000PT	VIP-1120PT	VIP-2140PT	
Product Image					
Hardware	Ethernet Port (RJ45)	1 WAN	1 WAN	1 WAN + 1 LAN	1 WAN + 1 LAN
	PoE	-	●	●	●
	Gigabit	-	-	-	●
	HD Audio	●	●	●	●
	Line Keys	-	-	2	-
	Soft Keys	-	-	4	4
	DSS Keys	20	20	-	6
Voice Features	LCD Display	-	-	2.4" TFT-LCD	2.8"+2.4" TFT-LCD
	SIP Account	1	1	2	4
	FoIP	-	-	-	-
	Voice Codec	G.711, G.723, G.722, G.729a/b	G.711, G.723, G.722, G.729a/b	G.711, G.722, G.723, G.726, G.729	G.711, G.722, G.723, G.726, G.729
Telephone Features	Video Codec	-	-	-	-
	3-way Conferencing	●	●	●	●
	Caller ID	●	●	●	●
	Call Mute/Holding	●	●	●	●
	Call Waiting	●	●	●	●
	Call Forward/Transfer	●	●	●	●
	Call History	●	●	●	●
	Do Not Disturb (DND)	●	●	●	●
	Hotline/Speed Dial	●	●	●	●
	Phonebook	●	●	●	●
	Message Waiting Indicator (MWI)	-	-	●	●
	Auto-Provisioning	●	●	●	●
	TR-069	●	●	●	●
	QoS	-	-	●	●
	Web call	-	-	●	●
	BLF	-	-	-	●
	Auto Answer (Intercom)	●	●	●	●
	Recording	-	-	-	-
	Media Player	-	-	-	-
	Ext. Console	-	-	-	-
	Photo Frame	-	-	●	●
	VPN (PPTP/L2TP)	●	●	L2TP, Open VPN	L2TP, Open VPN
	802.1Q VLAN	●	●	●	●

High Definition IP Phones

IP Phones					
Model	VIP-5060PT	VIP-6040PT	VIP-8030NT	ICF-1800	
Product Image					
Hardware	Ethernet Port (RJ45)	1 WAN + 1 LAN (Gigabit)	1 WAN + 1LAN (Gigabit)	1 WAN + 1LAN	1 WAN + 1 LAN
	PoE	●	●	-	●
	Gigabit	●	●	-	●
	HD Audio	●	●	●	●
	Line Keys	4	4	3	●
	Soft Keys	4	4	4	●
	DSS Keys	8	10	-	●
Voice Features	LCD Display	128 x 64 Graphic	3.5" TFT-LCD, 480 x 320 pixels	128 x 64 pixels	7" TFT LCD, 800 x 480 pixels
	SIP Account	6	4	3	6
	FoIP	-	-	-	-
	Voice Codec	G.711, G.722, G.723, G.726, G.729	G.711, G.722, G.723, G.726, G.729	G.711, G.723, G.726, G.729, GSM	G.711, G.723, G.729a/b
	Video Codec	-	-	-	H.263, H.264
Telephone Features	3-way Conferencing	●	5-way	●	●
	Caller ID	●	Caller ID Photo	●	●
	Call Mute/Holding	●	●	●	●
	Call Waiting	●	●	●	●
	Call Forward/Transfer	●	●	●	●
	Call History	●	●	●	●
	Do Not Disturb (DND)	●	●	●	●
	Hotline/Speed Dial	●	●	●	●
	Phonebook	●	●	●	●
	Message Waiting Indicator (MWI)	●	●	-	●
	Auto-Provisioning	●	●	●	●
	TR-069	●	●	●	●
	QoS	●	●	●	●
	Web call	●	-	-	●
	BLF	●	●	-	●
	Auto Answer (Intercom)	●	●	●	●
	Recording	-	-	●	●
	Media Player	-	-	-	●
	Ext. Console	VIP-EXT-26	VIP-EXT-40	-	-
	Photo Frame	-	-	-	●
	VPN (PPTP/L2TP)	- / ●	-	-	●
	802.1Q VLAN	●	●	●	●

High Performance **Asterisk-based** IP PBX

30
user registrations



▶ **IPX-330**

100
user registrations



▶ **IPX-2100**

200
user registrations



▶ **IPX-2200**

500
user registrations



▶ **IPX-2500**

SOHO (30 people)

SMB (100 people)

SME (200 people)

Enterprise (500 people)

Internet Telephony PBX System

IP PBX					
Model		IPX-330	IPX-2100	IPX-2200	IPX-2500
Product Image					
Hardware	Ethernet Port (RJ45)	1 WAN + 1 LAN	1 WAN + 1 LAN	1 WAN + 1 LAN	1 WAN + 1 LAN
	Expansion Slot	-	2	2	2
	HDD	-	-	-	●
	FXS	-	4 (IPX-21SL)	4 (IPX-21SL)	4 (IPX-21SL)
	FXO	2	8 (IPX-21FO)	8 (IPX-21FO)	8 (IPX-21FO)
	GSM	-	8 (IPX-21GS)	8 (IPX-21GS)	8 (IPX-21GS)
	Life-line	-	IPX-21SL	IPX-21SL	IPX-21SL
	IP Stack	No limit	No limit	No Limit	No limit
Voice Features	SIP (RFC3261)	●	●	●	●
	SIP Account	30	100	200	500
	Voice Line	15	30	60	100
	FoIP	T.30/T.38 Relay	T.30/T.38 Relay	T.30/T.38 Relay	T.30/T.38 Relay
	VAD/CNG/G.168 Echo Cancellation	●	●	●	●
	Audio Codec	G.711, G.722, G.726, G.729, GSM, Speex			
	Video Codec	H.261, H.263, H.263+, H.264			
	DTMF	In-Band, Out-of-band (RFC-2833), SIP Info (RFC-2976)			
Telephone Features	NAT Traversal	●	●	●	●
	Call Hold/Forward/Transfer	●	●	●	●
	DND (Do Not Disturb)	●	●	●	●
	Auto Attendant (AA)	●	●	●	●
	IVR/CDR	●	●	●	●
	Voice Mail/Voice Mail to e-mail	●	●	●	●
	Music on Hold	●	●	●	●
	Call Park/Call Pick Up	●	●	●	●
	Meet-Me Conference	●	●	●	●
	System Save/Backup	●	●	●	●
	SNMP	●	●	●	●
	VPN Server	●	●	●	●
	VPN Client	●	●	●	●
	Call Monitor	●	●	●	●
	DISA	●	●	●	●
	BLF	●	●	●	●
	Fax to Email/Email to Fax	●	●	●	●
	Call Paging and Intercom	●	●	●	●
	IPv6	●	●	●	●
	Real-time Voice Port Status	●	●	●	●

Voice Gateways

VoIP Gateways									
Model		VGW-400FO	VGW-400FS	VGW-402	VGW-800FO	VGW-800FS	VGW-804	VIP-2100	VIP-2400
Product Image									
Hardware	Ethernet port (RJ45)	1 WAN + 1 LAN	1 WAN + 1 LAN	1 WAN + 1 LAN	1 WAN + 1 LAN	1 WAN + 1 LAN	1 WAN + 1 LAN	2 LAN	2 LAN
	FXS	-	4	2	-	8	4	-	-
	FXO	4	-	2	8	-	4	-	-
	ISDN/PSTN/GSM	-	-	-	-	-	-	1 (PRI)	4 (PRI)
Voice Features	Life-line	-	-	●	-	-	●	-	-
	H.323 v4	-	-	-	-	-	-	●	●
	SIP (RFC3261)	●	●	●	●	●	●	●	●
	SIP Account	-	4	2	-	8	4	-	-
	Voice Line	4	4	4	8	8	8	-	-
	FoIP	T.38 or Fax Relay			T.38 or Fax Relay	T.38 or Fax Relay	T.38 or Fax Relay	T.38 Relay	
	VAD/CNG/G.168 Echo Cancellation	●	●	●	●	●	●	●	●
	Codec	G.711, G.723, G.729							
	DTMF	In-Band, Out-of-band (RFC-2833), SIP Info (RFC-2976)						Transparent, H.245 signal/alphanumeric, H.323 Q.931 UUI, RFC 2833, SIP Info	
	NAT Traversal	STUN, UPNP and Behind NAT							
Telephone Features	Call Hold/Forward/Transfer	●	●	●	●	●	●	●	●
	DND (Do Not Disturb)	-	-	-	-	-	-	-	-
	Hot Line/Speed Dial	● / -	● / -	● / -	●	-	● / -	-	-
	Dial Plan	●	●	●	●	●	●	●	●
	DDNS	●	●	●	●	●	●	●	●
	DDNS Server	●	●	●	●	●	●	●	●
	Dynamic Jitter Buffer	●	●	●	●	●	●	●	●
	Wizard Setup	-	-	-	-	-	-	-	-
	Management	Web, Auto-Provision, Telnet			●	●	●	Console, Telnet	Console, Telnet
	Save/Backup	●	●	●	●	●	●	●	●
	NAT Router	●	●	●	●	●	●	-	-
	Real-time Voice Port Status	●	●	●	●	●	●	-	-
	Tos/Diffserv	●	●	●	●	●	●	-	-
	Different Management Level	3 Levels	3 Levels	3 Levels	3 Levels	3 Levels	3 Levels	-	-
	Port Forward	●	●	●	●	●	●	-	-
	Contact Filter	●	●	●	●	●	●	-	-
SIP Trunk	4	4	4	24	24	24	1	1	
IPv6	●	●	●	●	●	●	-	-	

Analog Telephone Adapters

ATAs		
Model	VIP-156/VIP-156PE	VIP-157S

Product Image



Hardware	Ethernet Port (RJ45)	1 WAN + 1 LAN	1 WAN + 1 LAN
	PoE	- / ●	-
	Wireless Interface	-	-
	FXS/FXO/PSTN (RJ11)	1 FXS	2 FXS
	Life-line	-	-
	USB	-	-
	Audio/Video output	-	-
	LCD Display	-	-
Voice Features	SIP Account	5	5 / 10
	FoIP	T.38	T.38
	Voice Codec	G.711, G.723, G.726, G.729, GSM	
Telephone Features	Video Codec	-	-
	3-way Conferencing	●	●
	Caller ID	●	●
	Call Mute/Hold	●	●
	Call Waiting	●	●
	Call Forward/Transfer	●	●
	Call History	-	-
	Do Not Disturb (DND)	●	●
	Hotline/Speed Dial	●	●
	Phonebook	●	●
	Message Waiting Indicator (MWI)	●	●
	Auto-Provisioning	●	●
	TR-069	●	●
	QoS	●	●
	Web Call	-	-
	BLF	-	-
	Auto Answer (Intercom)	●	●
	Recording	-	-
	Media Player	-	-
	Ext. Console	-	-

SIP IP Camera

Fixed Dome Type	
Model	ICA-4130S

Product Image



Sensor	1/2.5" Progressive CMOS
Lens	f = 3.6mm/F1.2
Viewing Angle	H: 96 degrees V: 72 degrees
Sensibility (Lux)	0.5 lux (Color) 0.1 lux (B/W)
Image Compression	H.264/MPEG4/MJPEG
CMOS Pixel	1.3 Mega-Pixel
Max Resolution	1280 x 960 (30fps) 1280 x 720 (30fps)
Pan/Tilt/Zoom	Digital Zoom
PoE	●
Built in Microphone	●
Audio In	●
Audio Codec	G.711
SIP 2.0 (RFC3261)	●
3GPP	●
DDNS	●
ONVIF	●
WDR	●
3D De-noise	●
Multi-Profile	●
IP Filter	●
Intelligent	Motion/Tampering/ Audio/Network Failure
Local Storage (card is not included)	mSD/SDHC card slot
Operating Temperature	-10°C to 60°C

Watch Live Surveillance Images via SIP IP Cameras



Motion Alarm



Video Phone

SIP Public Announcement Adapter with PoE

Model	VPA-100
-------	---------

Product Image



Hardware	Ethernet Port(RJ45)	2 x 10/100BASE-TX
	PoE	802.3af class3
	Headset Spec.	3.5 mm
	Headset Port	●
	Loudspeaker Port	SPK+, SPK-
Physical Interfaces	LAN1	Connect to internet and provides PoE function
	LAN2	Connect other devices for network expanding
	Microphone/speaker	3.5mm connector
	Terminal block	loud speaker, power supply, ground and output ports
	5V power supply	Max. 200mA
	3.3V power supply	Max. 500mA
	Digital Out	8mA
Protocols and Management	Protocol	UDP
	Voice algorithms	G.711 (A-law and μ-law) G.722/G.722.1/G.722.2 G.723 G.726 G.729 iLBC
	Echo cancellation	●
	noise suppression	●
	Adaptive Jitter Buffer	●
	SIP (RFC3261)	●
	Digital Output Port	4
	Remote Volume Configuration	●
	Turn DO on/off via Web	●
	Turn DO on/off via Phone Key	●
	One voice line	●
Features	Auto Answer	●
	Volume Adjustment	output, handset input and speaker input
	Full-duplex	●
	Incoming Ring	●
	Audio Output Mode	Speaker and Handset

SIP Public Announcement Adapter with PoE

PoE

Digital Output
OFF ON

VoIP
SIP

Paging & Intercom

Door Lock

Voice Router

VoIP Router	
Model	VIP-462DG

Product Image



Hardware	Networking Interface	1 WAN + 4 LAN
	PoE (Power over Ethernet)	-
	Wireless Interface	IEEE 802.11b/g
	FXS (Foreign eXchange Station)	1
	FXO (Foreign eXchange Office)	-
	PSTN (Public Switched Telephone Network)	1
	DECT (Digital Enhanced Cordless Telecommunications)	1
	Life-line	●
Voice Features	LCD Display	1.5" LCD, 65K (Based on DCT-101)
	SIP 2.0 (RFC3261)	●
	SIP Registration	2 (DECT, FXS)
	Voice Codec (ITU-T)	G.711, G723.1, G.729
	VAD (Voice Activity Detection)	●
	CNG (Comfort Noise Generation)	●
	G.168 Echo Cancellation	●
	Gain Control	●
Telephone Features	DTMF Detection/Generation	●
	Dynamic Jitter Buffer	●
	QoS	●
	3-way Conferencing	●
	Caller ID	●
	Call Mute	●
	Call Holding	●
	Call Waiting	●
	Call Forward (Immediate/Busy/No Answer)	●
	Call Transfer (Blind/Attended)	●
	Hotline	●
	Speed Dial	●
	Phonebook	●
	Call History	● (Based on DCT-101)
	Max. DECT Registration	5

MCU

Multipoint Control Units		
Model	MCU-1400	MCU-1900

Product Image



Hardware	CPU	Quad-Core Intel Xeon 2.0GHz	Quad-Core Intel Xeon 2.0GHz
	RAM	1GB	1GB
	USB	4	4
	Ethernet Port (RJ45)	2 LAN	2 LAN
Voice Features	SIP Account	50	200
	Voice Calls	20	60
	Video Calls	4	12
	Audio Codec	G.711, G.723, G.729	
	Video Codec	MPEG-4, H.263, H.263 plus	
	DTMF	In-Band, Out-of-Band (RFC-2833), SIP Info	
	NAT Traversal	●	●
	Called ID	●	●
Telephone/Video Features	Call Hold	●	●
	Call Forward	●	●
	Call Transfer	●	●
	Call Pickup	●	●
	Call Park	●	●
	Video on Hold	●	●
	Music on Hold	●	●
	CDR	●	●
	Voice Mail	●	●
	Meet-Me Conferencing	●	●
	Call Monitor	●	●
	Call Transfer (Blind/Attended)	●	●
	Three-way voice conferencing	●	●
	Room Configuration	●	●
	Mute/Kick Function	●	●
	Voice/Video Recording	●	●
	Video MCU Screen Format	1:1, 1:4	1:1, 1:4, 1:6, 1:7, 1:8, 1:9
	Voice Room Number	3	9
	Video Room Number	1	3

UMG

Unified Office Gateway	
	UMG-1000

Product Image



Hardware	
Dimensions	13-inch, Desktop
Network Interface	1 x WAN - 10/100 3 x LAN - 10/100
Wireless AP Support	-
HDD Drive Bay	1 Internal Slot 2.5-inch SATA
Voice-FXO Ports	4 x FXO
Software	
Support Account	100
Concurrent Voice Calls	30
Voice Compression	G.711, G.726
Video Compression	H.261, H.263, H.263+, H.264
RAID	-
PPTP VPN	100 Tunnels
SSL VPN	8 Tunnels (Site-to-Site)
Protocol	POP3, SMTP, IMAP
Web Mail System	●
E-mail Accounts	100
Anti-Virus	●
Anti-Spam	●
Spanning Tree	-
IGMP Snooping	-



PLANET Technology Corporation

11F., No. 96, Minquan Rd., Xindian Dist., New Taipei City 231, Taiwan (R.O.C)
Tel: 886-2-2219-9518 Fax: 886-2-2219-9528 E-mail: sales@planet.com.tw