



CC2000: software for centralized and over IP datacenter management with single sign-on.

Enterprise solutions for centralized, remote and over IP datacenter and IT management.


Cat 5e/6 KVM switches and LCD KVM switches

- second console port
- rack mountable, 1U, dual rail LCD
- expandable up to 256 / 512 server
- multilingual and on-screen keyboard
- panel array mode and broadcast mode



| | Ports | Bus | LAN/WAN | Resolution |
|---------------------------|--------|-----|---------|-------------------|
| Cat 5e/6 LCD KVM switches | | | | |
| KL1508AN / KL1516AN | 8 / 16 | 1 | | up to 1280 x 1024 |
| KL1508AiN / KL1516AiN | 8 / 16 | 1 | V | up to 1280 x 1024 |
| Cat 5e/6 KVM switches | | | | |
| KH1508Ai / KH1516Ai | 8 / 16 | 1 | V | up to 1600 x 1200 |
| KH1508A / KH1516A | 8 / 16 | 1 | | up to 1600 x 1200 |
| KH2508A / KH2516A | 8 / 16 | 2 | | up to 1600 x 1200 |

Note: ATEN CPU modules offer HDMI, DisplayPort, DVI and VGA connectivity. (e.g. KA7170)




Access multiple servers / computers over IP.

Product
KL1516AiN



KVM over IP switches

- laptop USB console
- intelligent bus switching
- rack mountable, 1U / 2U
- energy saving fan speed control
- advanced security and user settings
- multilingual and on-screen keyboard
- panel array mode and broadcast mode
- PadClient for control via tablet (KN2/4/8 series)



| | Ports | Bus | Virtual media | Dual network Dual power | Resolution |
|----------------------|---------|-----|---------------|----------------------------|-------------------|
| KVM over IP switches | | | | | |
| KN1108V / KN1116V | 8 / 16 | 2 | V | V | up to 1920 x 1200 |
| KN2116A / KN2132 | 16 / 32 | 3 | | | up to 1600 x 1200 |
| KN2124V | 24 | 3 | V | V | up to 1600 x 1200 |
| KN4140V | 40 | 5 | V | V | up to 1600 x 1200 |
| KN2116VA / KN2132VA | 16 / 32 | 3 | V | V | up to 1920 x 1200 |
| KN4116VA / KN4164V | 16 / 64 | 5 | V | V | up to 1920 x 1200 |
| KN8132V / KN8164V | 32 / 64 | 9 | V | V | up to 1920 x 1200 |

Note: ATEN CPU modules offer HDMI, DisplayPort, DVI and VGA connectivity. (e.g. KA7166)

Several users manage and access multiple servers over IP simultaneously.


**Product
KN8164V**



KVM over IP extenders

- push video
- virtual media
- unlimited scalability
- remote control via OSD, hotkeys
- advanced security and user settings
- videowall function (up to 64 displays)
- CCKM matrix manager lite software included

..... Network — Video / Audio / USB — KVM + Audio



Unlimited scalability

Remote console

Port / Console

Interface

Resolution

Distance

KVM over IP extenders

KE6900

1 / 2

DVI-I

up to 1920 x 1200

LAN

KE6940

1 / 2

DVI-I

up to 1920 x 1200, dual view

LAN

Note: Transmitter and receiver are also available separately.

Access any computer from any console within a local network.


Product
KE6940



Serial over IP console servers

- data buffering
- laptop USB console
- rack mountable, 1U
- multi-user simultaneous access
- advanced security and user settings

| | Ports | USB | Dual network Dual power |
|--------------------------------|---------|-----|----------------------------|
| Serial over IP console servers | | | |
| SN3101 | 1 | | |
| SN0116 | 16 | | |
| SN9108 / SN9116 | 8 / 16 | | |
| SN0108A / SN0116A | 8 / 16 | 3 | V |
| SN0132 / SN0148 | 32 / 48 | 3 | V |




Access several serial devices from any location over IP through a secure serial connection.

Product SN0148



KVM matrix switches

- push video
- virtual media
- closed circuit
- rack mountable, 1U
- up to 18 consoles (KA7178)
- advanced security and user settings
- remote control via GUI, hotkeys and OSD



Access and manage several servers from multiple consoles within a closed circuit.


**Product
KM0932**



Note: ATEN CPU modules offer HDMI, DisplayPort, DVI and VGA connectivity. (e.g. KA7166 and KA7178)

Centralized over IP power management

- rack mountable, 1U
- environment sensors
- metered and / or switched
- critical overload protection
- eco Sensors management software included
- power consumption monitoring and analysis



| | Outlet sockets | Metered | Switched | Electric current |
|---------|-----------------|---------|----------|------------------|
| eco PDU | | | | |
| PE5108G | 8x C13 | bank | | 10 Amp |
| PE5208G | 7x C13 + 1x C19 | bank | | 16 Amp |
| PE7108G | 8x C13 | outlet | | 10 Amp |
| PE7208G | 7x C13 + 1x C19 | outlet | | 16 Amp |
| PE6108G | 8x C13 | bank | outlet | 10 Amp |
| PE6208G | 7x C13 + 1x C19 | bank | outlet | 16 Amp |
| PE8108G | 8x C13 | outlet | outlet | 10 Amp |
| PE8208G | 7x C13 + 1x C19 | outlet | outlet | 16 Amp |

Control, measure and analyse the power of several devices from any location over IP.

Product
PE5108G



Total datacenter management solution

ATEN provides management solutions for any SMB- and enterprise-sized IT setup which allows computers and servers to be managed locally or remotely from multiple local networks or from any location over IP, while also keeping an eye on power-consumption.

