

57535-2

Copper Cable, category 5e, 4 pair, UTP, PVC, 24 AWG solid, 305 m pull-box, white

Body Features

Jacket Material	PVC
Jacket Color	White
Conductor Material	Copper
Insulation Material	PE
Wire Color	White

Configuration Features

Number of Pairs	4
Number of Conductors	8

Dimensions

Overall Outside Diameter	5.100 mm 0.201 in
Conductor Diameter	.546 mm
Length	305.00 m 1000.66 ft
Wire Size (CMA)	24 AWG

Electrical Specifications

ANSI/TIA Category	5e
-------------------	----

General Specifications

Cable Type	U/UTP (unshielded)
------------	--------------------

Industry Standards

Flammability Rating	PVC
---------------------	-----

Packaging Features

Packaging Method	Pull Box
Packaging Quantity	305

Product Availability

Region	EMEA
--------	------

Product Type Features

Cable Style	Simplex
Product Classification	Cable - ISO/IEC Category
Product Type	Cable
Shielded	No
System	AMP NETCONNECT
Wire/Cable Type	Twisted Pair

57535-2

Usage Conditions

Operating Temperature Range -20 – 60 °C

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

Classification

Compliant