



# Application Guide

Delivering a variety of efficient networking applications

# Hotels & Resorts

Comprehensive networking equipment to satisfy customer comfort and management efficiency

PLANET hotels and resorts application provides a comprehensive collection of products to satisfy the comfort and security of guests and at the same time makes operation and management efficient. A wide range of devices including management switch, IP-PBX, IP phone, wireless AP controller, indoor and outdoor APs, SIP broadcasting system and SIP door intercom are reliable to ensure high-quality data, voice and power communications for the whole hospitality industry.

## Network Infrastructures

### Vehicle 4G LTE Cellular Wireless Gateway VCG-1500WG-LTE

- One SIM slot and one 4G LTE antenna for network connection
- Supports Wi-Fi 802.11 b/g/n for mobile client connectivity
- GPS antenna allows to detect the location via sat nav system
- Supports CMS for remote management
- Supports GRE, PPTP, IPSec and L2TP



### 24-Port Ultra PoE + 4-Port 10G LCD Switch GS-5220-24UP4XVR

- 10/100/1000BASE-T with 24 802.3bt PoE ports
- Four 1G/10G SFP+ ports
- 400-/600-watt PoE budget
- Up to 75 watts per PoE port
- R model supports 100~240V AC/48~60V DC redundant power



## Wireless

### In-Wall 2.4GHz 300Mbps Wi-Fi AP WNAP-W2200UE

- 10/100BASE-TX ports, with one 802.3af PoE/PD port supported
- 802.1Q VLAN mapping multiple SSIDs
- AP router, universal repeater, WISP mode
- In-wall design with USB charger port
- Centrally managed by PLANET WAPC series and Software AP Controller



### Dual Band 1200Mbps Ceiling-mount Wi-Fi AP WDAP-C7200E

- Simultaneous dual-band connectivity in 2.4GHz (300Mbps) and 5GHz (867Mbps)
- Gigabit Ethernet ports, 802.3at PoE/PD supported
- 802.1Q VLAN mapping multiple SSIDs
- AP router, universal repeater, WISP mode
- Centrally managed by PLANET WAPC series and software-based AP controller



### Wireless AP Controller (1000APs) WAPC-1000

- AP auto-discovery
- Control up to 1024/APs
- Central provisioning and cluster management
- Easy deployment with map positioning
- Real-time AP status monitoring
- Built-in RADIUS server seamlessly integrated into the enterprise network
- Profile creation and maintenance



## Surveillance

### 1080p IR Bullet/Dome PoE IP Camera ICA-4250

- 3.6mm lens with 74 degrees angle view
- Maximum resolution 1920 x 1080 (30fps)
- 25-meter IR LEDs with ICR
- WDR, 2DNR, IP66
- Cable management



### 1080p IR Bullet/Dome PoE IP Camera ICA-3250

- 3.6mm lens with 74 degrees angle view
- Maximum resolution 1920 x 1080 (30fps)
- 20-meter IR LEDs with ICR
- WDR, 2DNR, IP66



### 4/8/16-Channel Hybrid Digital Video Recorder HDVR-1630

- Records 60fps @1920 x 1080
- Maximum bitrate 60Mbps
- 16-ch BNC connectors and 1 x SATA HDD
- 1920 x 1080 HDMI and VGA local display



## Voice Communications

### High Definition Color PoE IP Phone VIP-1120PT

- 2.4-inch color LCD monitor
- 2-line key with color LED
- 2 SIP identities
- Wideband G.722 HD audio
- IEEE 802.3at/af PoE compliant
- QoS, TR069, auto-provisioning and multi-language



### IP65 720p SIP Door Intercom w/RFID HDP-5240PT

- 720p HD camera with viewing angle: 110°, 95°
- Wideband G.722 HD audio
- Trouble-free installation
- IP65 for eaves environment
- -20 to 60 degrees C operating temperature
- Unlock the door with an RFID, remote DTMF or local password



### SIP Public Announcement Adapter with PoE VPA-100

- Supports SIP 2.0 (RFC 3261)
- IEEE 802.3af Power over Ethernet compliant
- Paging and intercom
- Four programmable output ports
- Audio output mode: Speaker and handset
- Microphone/speaker: 3.5mm connector





## Outdoor Facility



1080p IR Bullet/Dome  
PoE IP Camera  
**ICA-3250**

## Guestrooms



HD Color PoE IP Phone  
**VIP-1120PT**

## Office



In-Wall 2.4GHz 300Mbps  
Wi-Fi AP  
**WNAP-W2200UE**

## Corridor



Dual Band Ceiling-mount  
Wi-Fi AP  
**WNAP-C3220E**

## Control Room



24-Port Ultra PoE + 4-Port  
10G LCD Switch  
**GS-5220-24UP4XVR**




Wireless AP Controller  
(1000APs)  
**WAPC-1000**



4/8/16-Channel Hybrid  
Digital Video Recorder  
**HDVR-1630**



Internet Telephony PBX  
System  
**IPX-2500**



SIP Public Announcement  
Adapter with PoE  
**VPA-100**

## Hotel Lobby



1080p IR Bullet/Dome  
PoE IP Camera  
**ICA-4250**



Dual Band 1200Mbps  
Ceiling-mount Wi-Fi AP  
**WDAP-C7200E**



IP65 720p SIP Door  
Intercom w/RFID  
**HDP-5240PT**



Vehicle 4G LTE Cellular  
Wireless Gateway  
**VCG-1500WG-LTE**

## Entrance

## Shuttle Bus



# Digital Campus

Efficient management and extension of campus network capacity, mobility and security

As technology advances rapidly these days, how to create an efficient and reliable network application became an important issue for campus and educational network deployment. PLANET campus network solution offers a highly-integrated series of products ranging from wireless LAN, network backbone switches, network security, IP Surveillance to VoIP products that are closely interconnected to ensure the mobility to access the internet from anywhere, the security of the wired and the wireless connections and the efficiency of campus IoT structure.

## Network Infrastructures

### 24-port PoE+4-port 10G LCD Switch GS-5220-24UP4XV

- 10/100/1000BASE-T with 802.3bt Ultra PoE port x 24
- 1G/10G SFP+ port x 4
- 400-/600-watt PoE budget
- Up to 75 watts per PoE port
- R model supports 100~240V AC/48~60V DC redundant power



### Layer 3 12-port 10G SFP+ Fiber Switch XGS-6350-12X8TR

- 1G/10G SFP+ port x 12
- 10/100/1000BASE-T port x 8
- Dual 100~240V AC redundant power
- Built-in RADIUS client to co-operate with the RADIUS Server for IPv4 and IPv6



### 24-port 1000X+4-10G Stack Switch SGS-6341-16S8C4XR

- 10/1000BASE-X SFP port x 24
- 10/100/1000BASE-T port x 8 shared with Port-21 to Port-24
- 10GBASE-X SFP+ port x 4
- 100~240V AC and 12V DC redundant power system
- Smart fan design for silent operation



## Wireless

### Dual Band 1200Mbps Ceiling-mount Wi-Fi AP WDAP-C7200E

- Simultaneous dual-band connectivity in 2.4GHz 300Mbps and 5GHz 867Mbps
- Gigabit Ethernet ports, 802.3at PoE/PD supported
- 802.1Q VLAN mapping to multiple SSIDs
- AP router, universal repeater, WISP mode
- Centrally managed by PLANET WAPC series and Software AP Controller



### IP68 Dual Band 1200Mbps Wi-Fi AP WDAP-802AC

- Gigabit wire and 1200Mbps wireless connectivity (dual-band)
- 4 built-in N-type (F) antenna connectors
- 802.1Q VLAN mapping to multiple SSIDs
- Ground terminal design, IP68 rating
- 802.3at Power over Ethernet
- Centrally managed by PLANET WAPC series and Software AP Controller



### Wireless AP Controller WAPC-500

- AP auto-discovery
- Control up to 512/APs
- Central provisioning and cluster management
- Easy deployment with map positioning
- Real-time AP status monitoring
- Built-in RADIUS server seamlessly integrated into the enterprise network
- Profile creation and maintenance



## Surveillance

### 1080p IR Bullet/Dome PoE IP Camera ICA-3250

- 3.6mm lens with 74 degrees angle view
- Maximum resolution 1920 x 1080 (30fps)
- 20-meter IR LEDs with ICR
- WDR, 2DNR, IP66



### Media Converter Chassis (10G Converter) MC-1500R (XT-705A)

- Hot-swappable Feature on each Slot
- FT-80x/FT-90x/FT-1105A/FT-1205A compatible
- 10/19-inch Rack mountable
- AC/DC Hot-swappable Redundant Power



## Voice Communication

### 7-inch SIP Conferencing Phone ICF-1800

- Built-in Android 4.2 OS multimedia conferencing phone
- 7-inch TFT color multi touch screen
- 6 identities/accounts
- Wideband G.722 HD audio with handset and hands-free features
- Dual 10/100/1000 Gigabit Ethernet
- Titatable 2 megapixel CMOS camera, HDMI, micro SD



### IP65 720p SIP Door Intercom w/RFID HDP-5240PT

- 720p HD camera with viewing angle: 110°, 95°
- Wideband G.722 HD audio
- Trouble-free installation
- IP65 for eaves environment
- -20 to 60 degrees C operating temperature
- Unlock the door with an RFID, remote DTMF or local password



### SIP IP Phone w/Color Screen VIP-2140PT

- 2.8-inch main color LCD monitor
- 2.4-inch (DSS) key-mapping LCD monitor
- 4 identities/accounts with color LED
- 30 configurable and 6 multicolored LED keys
- Wideband G.722 HD audio with handset and hands-free features
- Dual 10/100/1000 Gigabit Ethernet





## Library / Student Center



48-port+4-port 10G Stack Switch  
**SGS-6341-48T4X**



24-port PoE+4-10G Stack Switch  
**SGS-6341-24P4X**



SIP IP Phone w/Color Screen  
**VIP-2140PT**



IP67 5GHz 300Mbps Wi-Fi AP  
**WAP-552N**



Dual Band 1200Mbps Ceiling-mount Wi-Fi AP  
**WDAP-C7200E**

## Academic Classroom



Layer 3 24-port SFP+4-port 10G Stack Switch  
**XGS3-24242**



Media Converter Chassis (10G Converter)  
**MC-1500R**



Layer 3 12-port 10G SFP+ Fiber Switch  
**XGS-6350-12X8TR**



Dual Band 1200Mbps Ceiling-mount Wi-Fi AP  
**WDAP-C7200E**

## Outdoor Facility



Renewable Energy PoE Switch  
**BSP-360**



IP55 5GHz 300Mbps Wi-Fi CPE  
**WBS-502N**



IP68 Dual Band 1200Mbps Wi-Fi AP  
**WDAP-802AC**



1080p IR Bullet/Dome PoE IP Camera  
**ICA-3250**

## Gym



Dual Band 1200Mbps Ceiling-mount Wi-Fi AP  
**WDAP-C7200E**



IP67 5GHz 300Mbps Wi-Fi AP  
**WAP-552N**



24-port 1000X+4-10G Stack Switch  
**SGS-6341-16S8C4XR**

## Administration Office Building



24-port PoE+4-port 10G LCD Switch  
**GS-5220-24UP4XV**



Wireless AP Controller  
**WAPC-500**



Dual Band 1200Mbps Ceiling-mount Wi-Fi AP  
**WDAP-C7200E**



7-inch SIP Conferencing Phone  
**ICF-1800**



IP65 720p SIP Door Intercom w/RFID  
**HDP-5240PT**

# Enterprise-Smart Building

## Facilitate smart networking system with PLANET enterprise application

To make a network of smart buildings a reality, PLANET enterprise applications provide closely controlled security within your networking system, and at the same time, they make the digital network design efficient and cost-effective. PLANET provides data centers of office buildings, banks, etc. with specially-designed color touch LCD Ethernet switches, large-scale wireless LAN controllers, network video recorders and security gateways. By utilizing our latest Network Management System (UNI-NMS,) demands for fast and safe digital transmission through the IP deployments including VoIP system, IP surveillance and wireless LAN can be centrally managed and easily controlled to ensure optimal capability and performance.

### Control Center

#### Universal Network Management System UNI-NMS

- Detect a maximum of 100,000 nodes
- Up to 200 sites, 200 floor maps, 500 nodes per area
- Easy to keep track of the status of each device
- Display of the topology of network devices
- Any fault found can be made known
- Real-time signal coverage of APs



### Meeting Room

#### HD Touch Screen Android Multimedia Conferencing Phone ICF-1800

- Built-in Android 4.2 OS multimedia conferencing phone
- 7-inch TFT color multi touch screen
- 6 identities/accounts
- Wideband G.722 HD audio with handset and hands-free
- Dual 10/100/1000 Gigabit Ethernet
- Tillable 2 megapixel CMOS camera, HDMI, micro SD



### Work Space

#### 2.4GHz 300Mbps Wi-Fi AP WNAP-C3220E

- 10/100BASE-TX port, 802.3af PoE/PD supported
- 802.1Q VLAN mapping of multiple SSIDs
- Access Point, Gateway, Repeater, WDS (AP/Bridge/Station) modes
- Centrally managed by PLANET WAPC series and Software AP Controller, UNI-NMS



#### In-Wall 2.4GHz 300Mbps Wi-Fi AP WNAP-W2200UE

- 10/100BASE-TX ports, with one 802.3af PoE/PD port supported
- 802.1Q VLAN mapping of multiple SSIDs
- Access Point, Gateway, Repeater, WDS (AP/Bridge/Station) modes
- In-wall design with USB charger port
- Centrally managed by PLANET WAPC series and Software AP Controller, UNI-NMS



#### SIP IP Phone w/Color Screen VIP-2140PT

- 2.8-inch main color LCD monitor
- 2.4-inch (DSS) key-mapping LCD monitor
- 4 identities/accounts with color LED
- 30 configurable and 6 multicolored LED keys
- Wideband G.722 HD audio with handset and hands-free speaker
- Dual 10/100/1000 Gigabit Ethernet



### Entrance

#### 1080p IR Bullet/Dome PoE IP Camera ICA-3250/ICA-4250

- 3.6mm lens with 74 degrees angle view
- Maximum resolution 1920 x 1080 (30fps)
- 20-meter IR LEDs with ICR
- WDR, 2DNR, IP66



#### Internet Telephony PBX System IPX-2200

- 60 concurrent calls and up to 200 registers
- 36 concurrent calls and up to 40 conference rooms
- Recording/Voicemail up to 1,500 hours
- 2 slots for maximum 8 ports for FXO/GSM
- 10/100/1000 Gigabit Ethernet



### Data Center

#### Layer 3 Chassis Routing Switch XGS3-42000R

- 160-port 10/100/1000BASE-T copper
- 156 1000BASE-SX/LX SFP fiber slots
- 60 10G XFP fiber slots
- 6 40G QSFP+ fiber slots
- 19-inch, 6U rack-mount



#### 24-port PoE + 4-port 10G LCD Switch GS-5220-24P4XV

- 10/100/1000BASE-T with 802.3at PoE+ port x 24
- 1G/10G SFP+ port x 4
- 400-/600-watt PoE budget
- Up to 36 watts per PoE port
- R model supports 100~240V AC/48~60V DC redundant power



#### Network Video Recorder - 32-ch NVR-3685

- Supports VGA/HDMI dual local display
- Supports 8 SATA HDDs, up to 6TB per HDD
- Supports H.265/H.264 compression
- Supports RAID 0/1/5
- Location management with eMap
- Supports mobile phone remote view



#### Security Gateway CS-950

- Control up to 50 APs
- User authentication and MAC ACL
- Customized captive portal
- Unified security gateway with VPN connectivity
- Advanced anti-virus and anti-spam services
- IDP service and content filtering



#### Wireless AP Controller - 500APs WAPC-500

- AP auto-discovery
- Control up to 512 APs
- Central provisioning and cluster management
- Easy deployment with map positioning
- Real-time AP status monitoring
- Profile creation and maintenance





## Control Center



Universal Network  
Management System  
**UNI-NMS**

## Meeting Room



HD Touch Screen Android  
Multimedia Conferencing  
Phone  
**ICF-1800**

## Work Space



2.4GHz 300Mbps  
Wi-Fi AP  
**WNAP-C3220E**



In-Wall 2.4GHz  
300Mbps Wi-Fi AP  
**WNAP-W2200UE**



SIP IP Phone w/  
Color Screen  
**VIP-2140PT**

## Data Center



Layer 3 Chassis Routing  
Switch  
**XGS3-42000R**



Network Video Recorder -  
32-ch  
**NVR-3685**



Security Gateway  
**CS-950**



Wireless AP Controller -  
500APs  
**WAPC-500**



24-port PoE + 4-port  
10G LCD Switch  
**GS-5220-24P4XV**



Internet Telephony  
PBX System  
**IPX-2200**

## Entrance



1080p IR Bullet/Dome  
PoE IP Camera  
**ICA-3250/ICA-4250**



# Factory Automation

Designed for reliable, secure and smart industrial network Infrastructures

PLANET factory automation application is one of its many Industrial Ethernet Solutions that provide highly-reliable and smart solutions to ensure continuous and efficient operation for the IIoT environment. The Industrial Ethernet upgrades traditional, proprietary factory floor networks to a low-cost, high-performance, and scalable architecture. PLANET provides a complete product portfolio that is compliant with major IE protocols such as Modbus TCP, EtherCAT, and EN50155 for information level, control level, and device level in the Industrial Ethernet network.

## M2M Station

### Flat-type 4-port PoE LCD Router WGR-500-4PV

- 2.4-inch color LCD touch screen with management functions
- 4-port 10/100/1000BASE-T with 802.3at PoE+
- 802.1Q VLAN and IGMP proxy
- AP auto-discovery
- Real-time AP status monitoring
- Customized captive portal



### Industrial 4-port RS232/ RS422/ RS485 Media Converter ICS-2400T

- 4 RS232/422/485 port to 10/100BASE-TX
- IP30 metal case protection
- -40 to 75 degrees C operating temperature
- TCP Server/Client, UDP Client, Virtual COM, Telnet Server, Pair Connection Remote/Local Modes
- 12 to 48V DC, redundant power with polarity reverse protect function



### Dual Band 1200Mbps Ceiling-mount Wi-Fi AP WDAP-C7200E

- Simultaneous dual-band connectivity in 2.4GHz 300Mbps and 5GHz 867Mbps
- Gigabit Ethernet ports for 802.3at PoE PDs
- 802.1Q VLAN mapping of multiple SSIDs
- AP router, universal repeater, WISP mode
- Centrally managed by PLANET WAPC series and Software AP Controller



### Industrial 4-port PoE ++ Switch IGS-5225-4UP1T2S

- 4-port 10/100/1000BASE-T with 802.3bt/802.3at PoE
- 1-port 10/100/1000BASE-T
- 2-port 100/1000BASE-X SFP
- IPv6/IPv4 Web, Telnet and SNMP management
- 802.1Q VLAN, MSTP and IGMP snooping
- ERPS ring supported
- Static route supported
- -40 to 75 degrees C wide operating temperature
- DI and DO supported



### Industrial 1-port Modbus Gateway IMG-110T

- 1 RS422/RS485 port
- Built-in IP-based Web interface and Telnet interface for remote management
- RTU Master, RTU Slave, ASCII Master, and ASCII Slave operation modes
- 9-48V DC power input
- -40 to 75 degrees C operating temperature
- IP40 metal case



### 2 Mega-pixel IR PoE Plus Speed Dome IP Camera with Extended Support ICA-E6260

- Built-in microSD card slot for on-board storage
- 33x optical zooming, endless pan and tilt
- Maximum of 60fps at 1080p
- Weatherproof (IP67), vandalproof (IK09)
- Superior low light sensitivity
- WDR enhancement, 3D noise reduction
- Built-in PTZ auto tracking and enhanced intelligent video application



## Production Line

### 16-ch EtherCAT Slave I/O Module IECS-1116-DI

- Built-in isolated 16 digital inputs
- 2 x RJ45 bus interface
- LED indicators for the input status
- Removable terminal block connector
- Distance between stations up to 100m (100BASE-TX)
- EtherCAT conformance test tool verified



### 16-ch EtherCAT Slave I/O Module IECS-1116-DO

- Built-in isolated 16 digital outputs
- 2 x RJ45 bus interface
- LED indicators for the input status
- Removable terminal block connector
- Distance between stations up to 100m (100BASE-TX)
- EtherCAT conformance test tool verified



## Storage/Warehouse

### 64-ch Network Video Recorder NVR-E6480

- Manages up to 64 cameras
- 8-bay rackmount (2U) with software RAID (0,1)
- Instant playback in live view window
- Location-based management with eMap
- Supports dual stream management
- Remote access via mobile app, Web browser or CMS



### Industrial 16-port PoE Switch IGS-20160HPT

- 16-port 10/100/1000T with PoE+ plus 2-port 10/100/1000T + 2-port 10/100X SFP
- IPv6/IPv4 Web, Telnet and SNMP management
- 802.1Q VLAN, MSTP and IGMP snooping
- ERPS ring supported
- Static route supported
- -40 to 75 degrees C wide operating temperature
- DI and DO supported



### IP68/IK10 5MP Fisheye E-series Camera ICA-E8550

- 1.19mm fisheye lens for 180° and 360° panoramic wide angle view
- Built-in IR illuminators, effective up to 15 meters
- Vandalproof (IK10) and weatherproof (IP68)
- EN50155 compliance for professional
- ePTZ for data efficiency
- ICR, WDR and 3D noise reduction
- Mobile surveillance





## M2M Station



Dual Band 1200Mbps  
Ceiling-mount Wi-Fi AP  
**WDAP-C7200E**



IP68/IK10 5MP Fisheye  
E-series Camera  
**ICA-E8550**



Industrial 4-port PoE ++  
Switch  
**IGS-5225-4UP1T2S**



Industrial 4-port Serial  
Server  
**ICS-2400T**



Industrial 1-port  
Modbus Gateway  
**IMG-110T**



Flat-type 4-port PoE  
LCD Router  
**WGR-500-4PV**



Industrial 16-port PoE  
Switch  
**IGS-20160HPT**



64-ch Network Video  
Recorder  
**NVR-E6480**



2 Mega-pixel IR PoE Plus  
Speed Dome IP Camera  
with Extended Support  
**ICA-E6265**

## Production Line



16-ch EtherCAT Slave  
I/O Module  
**IECS-1116-DI**



16-ch EtherCAT Slave  
I/O Module  
**IECS-1116-DO**



# Intelligent Transportation System

Innovative transportation network with comprehensive IP solutions

PLANET covers a wide range of Intelligent Transportation System (ITS) applications for the railway, metro system and highway networking deployments. As all of these ITS network interfaces require long distance, high-bandwidth and real-time data transmission, PLANET's comprehensive product line provides robust, reliable and secure solutions to ensure uninterrupted high-quality transmission. Featuring ITU-T under G.8032 Recommendation, it provides sub-50ms protection and recovery switching for Ethernet traffic in a ring topology and at the same time ensures that there are no loops formed at the Ethernet layer.

## Metro System

### Platform/On the Train

#### 5 Mega-pixel Outdoor IR PoE Fisheye IP Camera with Extended Support ICA-E8550

- 1.19mm fisheye lens for 180° and 360° panoramic wide angle view
- ePTZ for data efficiency
- ICR, WDR and 3D noise reduction
- Built-in IR illuminators, effective up to 15 meters
- Built-in microSD card slot for on-board storage
- Vandalproof (IK10) and weatherproof (IP68)
- EN50155 compliance for professional mobile surveillance



#### 4-port PoE + 2-port TP Switch IGS-5226-4P2T

- IP50 metal case
- IEEE 1588 and synchronous Ethernet network timing
- IPv6/IPv4 Layer 3 static routing and route summarization
- 144-watt PoE budget, remote PoE power control
- 48~56V DC redundant power design
- ERPS Ring Data Recovery time < 50ms
- -40 to 75 degrees C wide operating temperature



#### EN50155 4G LTE/GPS/Wi-Fi Gateway VCG-1500WG-LTE

- 4 10/100TX LAN ports and 1 10/100TX WAN port
- One SIM slot and one 4G LTE antenna for network connection
- Supports Wi-Fi 802.11 b/g/n for mobile client connectivity
- GPS antenna allows to detect the location via sat nav system
- Supports NAT, DMZ, MAC/Application/IP filter and static routing
- Supports CMS and SNMP for remote management



### Gate

#### Industrial 1-/2-port RS422/485 Modbus Gateway IMG-120T

- 2 RS422/RS485 ports
- Built-in IP-based Web interface and Telnet interface for remote management
- RTU Master, RTU Slave, ASCII Master, and ASCII Slave operation modes
- 9-48V DC power input
- -40 to 75 degrees C operating temperature
- IP40 metal case



### Ticket Booth

#### Industrial 2-port RS232/RS422/RS485 Media Converter ICS-2200T

- 2 RS232/422/485 ports to 10/100 BASE-TX
- TCP Server/Client, UDP Client, Virtual COM, Telnet Server, Pair Connection-remote/local modes
- 12~48VDC, redundant power with polarity reverse protection function
- -40 to 75 degrees C operating temperature
- IP 30 metal case



### Control Center

#### Industrial 4-port PoE ++ Switch IGS-5225-4UP1T2S

- 4-port 10/100/1000BASE-T with 802.3bt/802.3at PoE
- 1-port 10/100/1000BASE-T
- 2-port 100/1000BASE-X SFP
- IPv6/IPv4 Web, Telnet and SNMP management
- 802.1Q VLAN, MSTP and IGMP snooping
- ERPS ring supported
- Static route supported
- -40 to 75 degrees C wide operating temperature
- DI and DO supported



## Railway

### Highway

#### Industrial 16-port LRP Switch LRP-104CET

- 1-port BNC with passive PoE PD
- 4-port 10/100TX RJ45 with IEEE 802.3at
- PoE+ PSE to remote PoE IP camera/AP
- -20 ~ 70 degrees C operating temperature



#### 2 Mega-pixel IR PoE Plus Speed Dome IP Camera with Extended Support ICA-E6265

- 36x optical zooming, endless pan & tilt
- Max. frame rate 60fps at 1080p
- Long distance adaptive IR LEDs
- Superior low light sensitivity
- WDR enhancement, 3D noise reduction
- Water-repellent and scratch-resistant lens glass
- Built-in PTZ auto tracking and enhanced intelligent video application



### Bus

#### Industrial 4G LTE/GPS Gateway ICG-2420G-LTE

- GPS and Google map supported
- Dual SIM cards for 3G/4G cellular network redundancy
- 3 10/100TX LAN ports and 1 10/100TX WAN port
- 2 DI and 1 DO ports, 2 RS232 and 1 RS485 serial ports
- Supports OpenVPN, IPSec
- -20 to 70 degrees C operating temperature
- IP40 aluminum case, DIN rail and fanless design



### Electric Box

#### 8-port LRP Managed Switch LRP-822CS

- 8 100Mbps BNC female ports with LRP Inject function
- 2 10/100/1000 BASE-T Gigabit RJ45 copper ports
- 2 100/1000 BASE-X mini-GBIC/SFP slots
- Supports PoE power up to 36W for each PoE port
- 802.1Q VLAN, MSTP and 1GMP Snooping
- IPv6/IPv4 ACL, QoS supported



### Control Center

#### Industrial Flat-type PoE Switch WGS-5225-8P2SV

- 2.4-inch color LCD touch screen with management functions
- 8-port 10/100/1000BASE-T with 802.3at PoE+
- 2-port 100/1000BASE-X SFP
- 802.1Q VLAN, MSTP and IGMP Snooping
- ERPS ring and IEEE 1588 supported
- Modbus TCP





## Gate



Industrial 1-/2-port RS422/  
485 Modbus Gateway  
**IMG-120T**

## Ticket Booth



Industrial 2-port RS232/  
RS422/RS485 Media  
Converter  
**ICS-2200T**

## Control Center



Industrial 4-port PoE ++  
Switch  
**IGS-5225-4UP1T2S**


## Highway



Industrial 16-port LRP  
Switch  
**LRP-104CET**



2 Mega-pixel IR PoE Plus  
Speed Dome IP Camera  
**ICA-E6265**



5 Mega-pixel Outdoor IR  
PoE Fisheye IP Camera  
with Extended Support  
**ICA-E8550**



4-port PoE + 2-port TP  
Switch  
**IGS-5226-4P2T**



EN50155 4G LTE/GPS/  
Wi-Fi Gateway  
**VCG-1500WG-LTE**

## Platform/On the Train



Industrial 4G LTE/GPS  
Gateway  
**ICG-2420G-LTE**

## Bus



Industrial Flat-type  
PoE Switch  
**WGS-5225-8P2SV**

## Control Center



8-port LRP Managed  
Switch  
**LRP-822CS**

## Electric Box



**PLANET Technology Corporation**

11F., No. 96, Minquan Rd., Xindian Dist., New Taipei City 231, Taiwan (R.O.C)  
Tel: 886-2-2219-9518 Fax: 886-2-2219-9528 E-mail: [sales@planet.com.tw](mailto:sales@planet.com.tw)

PLANET reserves the right to change specifications without prior notice. All brand names and trademarks are property of their respective owners. © PLANET Technology Corporation DM-AP0119