



## 2m UK 3 Pin to C19 Mains Cable, lead free

No.: 30459

UK 3 Pin Plug to IEC C19 Connector

### Description

UK 3 Pin to IEC C19 Mains Cable for use in professional areas and private sectors  
Provides max. 13A/250V, UK plug with 13A fuse  
Robust PVC housing and cable jacket, lead-free connectors [<0.1% lead in brass]  
High temperature resistance allows the cable to be used in non air-conditioned areas  
10 year warranty

Lindy Power Cables are high quality, reliable power delivery connections for use in a wide variety of professional and home environments.

This cable is ideal for the connection between a power distribution unit and the English electricity grid. Therefore, it is perfect for use in offices, control rooms and digital signage setups. Typically this kind of cable is utilized with devices that require higher current than an IEC C15 connector can provide.

The brass used in the connectors has a lead content of far below 0.1% and is therefore SVHC-free, as are all other materials used in these cables.

Please note that this cable is for use in dry areas only.

### Technical details

#### Connectors

Connector A: UK 3 Pin Plug

Connector B: IEC C19

Housing Material: PVC

Pin Construction:

A: Brass

B: Phosphor Bronze

Pin Plating: Nickel

Dimensions [approx.] WxDxH:

A: 48x69.5x21mm [1.89x2.74x0.83in]

B: 31.3x79x24mm [1.23x3.11x0.94in]

#### Cable Construction

Length: 2m [6.56ft]

Colour: Black

Conductor Material: Copper

Cable Material: H05-VVF 3G 1.5mm<sup>2</sup>

Number of Wires: 3  
Wire Gauge: 1.5mm<sup>2</sup>  
Jacket Diameter: 8.0mm (0.31in)  
Jacket Material: PVC

**Specifications**

Rated Voltage and Current: 13A/250V  
Operating Temperature: -10°C - 60°C (14°F - 140°F)  
Storage Temperature: -20°C - 70°C (-4°F - 158°F)

**Miscellaneous**

Packaging Type: Polybag  
Warranty (Years): 10  
Product Compliance: CE, RoHS, REACH, California Proposition 65

**Purchasing Information**

No.: 30459  
EAN: 4002888304597