



ATEN's USB Connectivity Series



**ATEN UC2322/
UC2324**
2/4-PORT USB-TO-SERIAL
RS-232 HUB

- Easy way to add 2 or 4 RS-232 serial ports
- Supports automatic handshake mode
- Up to 115.2 Kbps data transfer rate for each serial port
- Works with cellular phones, PDAs, digital cameras, modems and ISDN terminal adapters
- Dimensions (L x W x H) : 12.50 x 8.15 x 2.50 cm



**ATEN UC4852/
UC4854**
2/4-PORT USB-TO-SERIAL
RS-422/485 HUB

- Easy way to add 2 or 4 RS-422/RS-485 serial ports
- Each port can independently switch between RS-422 and RS-485
- Supports automatic handshake mode
- Works with cellular phones, PDAs, digital cameras, modems and ISDN terminal adapters
- Dimensions (L x W x H) : 12.50 x 8.15 x 2.50 cm



ATEN UC232A
USB-TO-SERIAL
CONVERTER

- Support the RS232 Serial interface
- Up to 230Kbps data transfer rate
- Works with cellular phones, PDAs, digital cameras, modems or ISDN terminal adapter



ATEN UCE60
USB EXTENDER

- Provides support for any full-speed (12Mb/s) or low-speed (1.5Mb/s) USB devices
- Extends the transmission distance of a USB device up to 60m (198 ft) using Cat 5 cabling
- LED indicates when additional external power supply needed



ATEN UE250
USB 2.0 EXTENDER
CABLE

- Extends the distance to your USB device up to 5m
- No power adapter required
- USB specification version 2.0 compliant



**ATEN US221A/
US421A**
2/4-PORT USB 2.0
PERIPHERAL SWITCH

- Enables two or four computers to share a single USB peripheral device
- Simple port selection via pushbuttons, configuration utility, or Auto Switch function
- Auto Switch Function
- LED indicators display port focus
- Multiplatform support - Windows and Mac
- Dimensions (L x W x H) : 7.20 x 6.60 x 2.50 cm / 10.20 x 7.60 x 2.30 cm



ATEN Infotech NV
Mijnwerkerslaan 34 | 3550 Heusden-Zolder | Belgium
tel: +32 11 53 15 43 | fax: +32 11 53 15 44
marketing@aten.be | www.aten.be

