

## Advanced Network Fixed Dome Camera

**DN-16058-1**  
**4016032292791**



## Always the best viewing angle due to the Smart Zoom function

Feeling safe is priceless. For this reason you should never compromise on security. Do we not have enough worries these days? Hand a part over: This camera is ideal for reliable indoor monitoring. The robust design raises no doubts that this might be a toy. The H.264 video standard ensures smooth, crystal clear images at a lower network load compared to legacy technologies. The high resolution offers even the tiniest details. The smart zoom function automatically activates the zoom lens as soon as motion is detected. This increases your awareness for the essential! Not only the hardware is convincing: With auto motion detection and supplied software your equipment is future-proof and you save a lot of time! Just focus on the essential instead of painstakingly going through the daily recordings! Video images are only generated in case of activity.

- 2.25x Optical Smart Zoom
- Smart Zoom: Zoom on the object that triggered the alarm
- Optical Zoom lens: f4.0mm - f9.0mm
- Viewing Angle: 75° - 36°
- High resolution and best video performance
- Enhanced motion detection and alarm notification functions
- Alarm and event notification by FTP and Email
- Powerful mobile surveillance supporting iPhone, Blackberry and WinCE devices
- Low-latency video streaming with H.264 compression format
- LAN Speed: 10/100Base-TX Ethernet
- Supported Protocols: DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP
- Frame Rate NTSC: 30, PAL: 25
- Number of Online Users: 10
- Security: Multiple user access levels with password protection
- Management by web browser or CMS software for up to 16 network cameras control simultaneously
- Compatible to the future proof ONVIF Standard
- Image Sensor: 1/3" HR color CCD sensor
- Resolution: 771x492 pixel NTSC / 753x582 pixel PAL
- Min Illumination 0.4 Lux / F1.8
- Shutter Speed 1/60 (1/50) to 1/100,000 sec.
- Operating Temperature: 0 °C - 40 °C
- Power Source (±10%): DC12V / 1.5A
- Dimensions (mm): 124.3(D) x 102(H)

### PACKAGE CONTENT

- IP Camera
- Manual
- Software CD
- RJ45 Adapter Cable



