

CentreCOM® GS900MX/MPX Series

LAYER 2 MANAGED GIGABIT ETHERNET STACKABLE SWITCHES

Allied Telesis CentreCOM GS900MX/MPX Series switches are cost-effective, fully managed, and stackable. The switches in this series can serve as an AMF node when an AMF Master switch is available in the network, which helps to reduce network running costs by automating and simplifying many day-to-day tasks.

With a choice of 24- and 48-port 10/100/1000T versions with 10G up link, Power over Ethernet (PoE), plus the ability to stack up to four units, the CentreCOM GS900MX/GS900MPX Series switches are ideal for demanding applications at the edge of the network.



Key Features

- » AMF node
The switch can serve as an AMF member
- » CLI support
- » Eco-friendly
- » Mixed hardware stacking up to four units
- » IPv6 basic features
- » IEEE 802.1x/MAC/Web authentication support

Specifications

Performance

- » 40Gbps of stacking bandwidth
- » Supports 9216bytes jumbo frames
- » Wirespeed multicasting
- » Up to 16K MAC addresses
- » 512MB DDR SDRAM
- » 64MB flash memory

Power Characteristics

- AT-GS924MX and AT-GS948MX
AC model: 100-240 VAC, 1.0A maximum, 50/60 Hz
AT-GS924MPX and AT-GS948MPX
AC model: 100-240 VAC, 5.0A maximum, 50/60 Hz

Expandability

- » Hardware stacking up to four units

Flexibility and Compatibility

- » Port speed and duplex configuration can be set manually or by auto-negotiation diagnostic tools
- » Automatic link flap detection and port shutdown
- » Optical Digital Diagnostics Monitoring (DDM)
- » Ping polling and TraceRoute for IPv4 and IPv6
- » Port mirroring

IP Features

- » Device management over IPv6 networks with SNMPv6, Telnetv6, SSHv6
- » NTPv6 client

Management

- » Front panel 7-segment LED provides at-a-glance status and fault information
- » Allied Telesis Management Framework™ (AMF) enables powerful centralized management and zerotouch device installation and recovery
- » Console management port on the front panel for ease of access
- » Eco-friendly mode allows ports and LEDs to be disabled to save power
- » Industry-standard CLI with context-sensitive help
- » Powerful CLI scripting engine
- » Comprehensive SNMP MIB support for standards-based device management
- » Built-in text editor
- » Event-based triggers allow user-defined scripts to be executed upon selected system events
- » USB interface allows software release files, configurations, and other files to be stored for backup and distribution to other devices

Quality of Service (QoS)

- » Eight priority queues with a hierarchy of high-priority queues for real-time traffic, and mixed scheduling, for each switch port
- » Limit bandwidth per port or per traffic class down to 64kbps
- » Wirespeed traffic classification with low latency essential for VoIP and real-time streaming media applications
- » Policy-based QoS based on VLAN, port, MAC and general packet classifiers
- » Policy-based storm protection
- » Extensive remarking capabilities
- » Taildrop for queue congestion control
- » Strict priority, weighted round robin or mixed scheduling
- » IP precedence and DiffServ marking based on Layer 2, 3 and 4 headers

Resiliency Features

- » Control Plane Prioritization (CPP) ensures the CPU always has sufficient bandwidth to process network control traffic
- » Dynamic link failover (host attach)
- » EPSRing™ (Ethernet Protection Switched Rings) with enhanced recovery
- » Loop protection: loop detection and thrash limiting
- » PVST+ compatibility mode
- » STP root guard

Security Features

- » Access Control Lists (ACLs) based on Layer 3 and 4 headers
- » Configurable auth-fail and guest VLANs
- » Authentication, Authorization, and Accounting (AAA)
- » Bootloader can be password protected for device security
- » BPDU protection
- » DHCP snooping, IP source guard and Dynamic ARP Inspection (DAI)
- » Dynamic VLAN assignment
- » Network Access and Control (NAC) features manage endpoint security
- » Port-based learn limits (intrusion detection)
- » Private VLANs provide security and port isolation for multiple customers using the same VLAN
- » Secure Copy (SCP)
- » Strong password security and encryption
- » Tri-authentication: MAC-based, Web-based and IEEE 802.1x



Specifications

Product	10/100/1000T (RJ-45) Copper Ports	Combo (100/1000X SFP Ports or 10/100/1000T, RJ-45 Ports)	10 Gigabit SFP+ Ports* or 10 Gigabit Stacking Ports	Max PoE+ Enabled Ports	Switching Fabric	Forwarding Rate
AT-GS924MX	24	2	2		92Gbps	68.44Mpps
AT-GS924MPX	24	2	2	24	92Gbps	68.44Mpps
AT-GS948MX	48	2	2		140Gbps	104.16Mpps
AT-GS948MPX	48	2	2	48	140Gbps	104.16Mpps

* 1G speed on SFP+ ports will be supported in a future release

Physical Specifications

PRODUCT	WIDTH	DEPTH	HEIGHT	WEIGHT
AT-GS924MX	339 mm (13.4 in)	211 mm (8.3 in)	44 mm (1.72 in)	2.5 Kg (5.5 lb)
AT-GS924MPX	441 mm (17.3 in)	356 mm (14 in)	44 mm (1.72 in)	5.3 Kg (11.6 lb)
AT-GS948MX	441 mm (17.3 in)	356 mm (14 in)	44 mm (1.72 in)	4.5 Kg (9.9 lb)
AT-GS948MPX	441 mm (17.3 in)	356 mm (14 in)	44 mm (1.72 in)	5.8 Kg (12.8 lb)

Power and Noise Characteristics

Product	No PoE Load				Full PoE+ Load				
	Max Power Consumption	Max Heat Dissipation	Typical Noise	Max Noise	Typical Power Consumption	Max Power Consumption	Max System Heat Dissipation	Typical Noise	Max Noise
AT-GS924MX	30.7W	104.6 BTU/hr	27.1 dB	52.7 dB					
AT-GS924MPX	53.6W	182.9 BTU/hr			464.3W	94.3W	321.7 BTU/hr	43.7 dB	57.7 dB
AT-GS948MX	50.7W	173.1 BTU/hr	33.8 dB	58.1 dB					
AT-GS948MPX	70.2W	239.5 BTU/hr			480.6W	110.6W	377.4 BTU/hr	42.0 dB	58.4 dB

PRODUCT	MAX POE POWER	MAX POE PORTS AT 7.5W PER PORT	MAX POE PORTS AT 15W PER PORT	MAX POE PORTS AT 30W PER PORT
AT-GS924MPX	370W	24	24	12
AT-GS948MPX	370W	48	24	12

Authentication

- RFC 1321 MD5 Message-Digest algorithm
RFC 1828 IP authentication using keyed MD5

Encryption

- | Encryption | |
|------------|---|
| FIPS 180-1 | Secure Hash standard (SHA-1) |
| FIPS 186 | Digital signature standard (RSA) |
| FIPS 46-3 | Data Encryption Standard (DES and 3DES) |

Ethernet

- IEEE 802.1AX Link aggregation (static and LACP)
 - IEEE 802.2 Logical Link Control (LLC)
 - IEEE 802.3 Ethernet
 - IEEE 802.3ab 1000T
 - IEEE 802.3ae 10 Gigabit Ethernet
 - IEEE 802.3ad Static and dynamic link aggregation
 - IEEE 802.3af Power over Ethernet (PoE)
 - IEEE 802.3at Power over Ethernet plus (PoE+)
 - IEEE 802.3az Energy Efficient Ethernet (EEE)
 - IEEE 802.3u 100X
 - IEEE 802.3x Flow control - full-duplex operation
 - IEEE 802.3z 1000X

IPv4 Features

- | | |
|---------|--|
| RFC 791 | Internet Protocol (IP) |
| RFC 792 | Internet Control Message Protocol (ICMP) |
| RFC 826 | Address Resolution Protocol (ARP) |
| RFC 894 | Standard for the transmission of IP datagrams over Ethernet networks |
| RFC 919 | Broadcasting Internet datagrams |
| RFC 922 | Broadcasting Internet datagrams in the presence of subnets |
| RFC 932 | Subnetwork addressing scheme |
| RFC 950 | Internet standard subnetting procedure |

- | | | | |
|---|---|----------|--|
| RFC 1042 | Standard for the transmission of IP datagrams over IEEE 802 networks | RFC 2013 | SNMPv2 MIB for UDP using SMIv2 |
| RFC 1071 | Computing the Internet checksum | RFC 2096 | IP forwarding table MIB |
| RFC 1122 | Internet host requirements | RFC 2578 | Structure of Management Information v2 (SMIv2) |
| RFC 1256 | ICMP router discovery messages | RFC 2579 | Textual conventions for SMIv2 |
| RFC 1518 | An architecture for IP address allocation with CIDR | RFC 2580 | Conformance statements for SMIv2 |
| RFC 1519 | Classless Inter-Domain Routing (CIDR) | RFC 2674 | Definitions of managed objects for bridges with traffic classes, multicast filtering and VLAN extensions |
| RFC 1918 | IP addressing | RFC 2741 | Agent extensibility (AgentX) protocol |
| IPv6 Features | | RFC 2819 | RMON MIB (groups 1,2,3 and 9) |
| RFC 2460 | IPv6 specification | RFC 2863 | Interfaces group MIB |
| RFC 2464 | Transmission of IPv6 packets over Ethernet networks | RFC 3164 | Syslog protocol |
| RFC 3484 | Default address selection for IPv6 | RFC 3411 | An architecture for describing SNMP management frameworks |
| RFC 3596 | DNS extensions to support IPv6 | RFC 3412 | Message processing and dispatching for the SNMP |
| RFC 4007 | IPv6 scoped address architecture | RFC 3413 | SNMP applications |
| RFC 4193 | Unique local IPv6 unicast addresses | RFC 3414 | User-based Security Model (USM) for SNMPv3 |
| RFC 4291 | IPv6 addressing architecture | RFC 3415 | View-based Access Control Model (VACM) for SNMP |
| RFC 4861 | Neighbor discovery for IPv6 | RFC 3416 | Version 2 of the protocol operations for the SNMP |
| RFC 4862 | IPv6 Stateless Address Auto-Configuration (SLAAC) | RFC 3417 | Transport mappings for the SNMP MIB for SNMP |
| RFC 5014 | IPv6 socket API for source address selection | RFC 3418 | Power over Ethernet (PoE) MIB |
| RFC 5095 | Deprecation of type 0 routing headers in IPv6 | RFC 3635 | Definitions of managed objects for the Ethernet-like interface types |
| Management | | RFC 3636 | IEEE 802.3 MAU MIB |
| AMF MIB and SNMP traps | | RFC 4188 | Definitions of managed objects for bridges |
| AT Enterprise MIB | | RFC 4318 | Definitions of managed objects for bridges with RSTP |
| SNMPv1, v2c and v3 | | RFC 4560 | Definitions of managed objects for remote ping, traceroute and lookup operations |
| IEEE 802.1AB Link Layer Discovery Protocol (LLDP) | | | |
| RFC 1155 | Structure and identification of management information for TCP/IP-based Internets | | |
| RFC 1157 | Simple Network Management Protocol (SNMP) | | |
| RFC 1212 | Concise MIB definitions | | |
| RFC 1213 | MIB for network management of TCP/IP-based Internets: MIB-II | | |
| RFC 1215 | Convention for defining traps for use with the SNMP | | |
| RFC 1227 | SNMP MUX protocol and MIB | | |
| RFC 1239 | Standard MIB | | |
| RFC 2011 | SNMPv2 MIB for IP using SMIv2 | | |
| RFC 2012 | SNMPv2 MIB for TCP using SMIv2 | | |
| Multicast Support | | | |
| IGMP snooping (v1, v2 and v3) | | | |
| IGMP snooping fast-leave | | | |
| MLD snooping (v1 and v2) | | | |

Multi-set Count

- Multicast Support**
IGMP snooping (v1, v2 and v3)
IGMP snooping fast-leave
MLD snooping (v1 and v2)

Quality of Service (QoS)

- IEEE 802.1p Priority tagging
- RFC 2211 Specification of the controlled-load network element service
- RFC 2474 DiffServ precedence for eight queues/port
- RFC 2475 DiffServ architecture
- RFC 2597 DiffServ Assured Forwarding (AF)
- RFC 2697 A single-rate three-color marker
- RFC 2698 A two-rate three-color marker
- RFC 3246 DiffServ Expedited Forwarding (EF)

Resiliency Features

- IEEE 802.1D MAC bridges
- IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
- IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)

Security Features

- SSH remote login
- SSLv2
- TACACS+ accounting and authentication
- IEEE 802.1X authentication protocols (TLS, TTLS, PEAP and MD5)
- IEEE 802.1X multi-supplicant authentication
- IEEE 802.1X port-based network access control
- RFC 2246 TLS protocol v1.0
- RFC 2865 RADIUS
- RFC 2866 RADIUS accounting
- RFC 2868 RADIUS attributes for tunnel protocol support
- RFC 3546 Transport Layer Security (TLS) extensions
- RFC 3579 RADIUS support for Extensible Authentication Protocol (EAP)
- RFC 3580 IEEE 802.1x RADIUS usage guidelines
- RFC 3748 PPP Extensible Authentication Protocol (EAP)
- RFC 4251 Secure Shell (SSHv2) protocol architecture
- RFC 4252 Secure Shell (SSHv2) authentication protocol
- RFC 4253 Secure Shell (SSHv2) transport layer protocol
- RFC 4254 Secure Shell (SSHv2) connection protocol

Services

- RFC 854 Telnet protocol specification
- RFC 855 Telnet option specifications
- RFC 857 Telnet echo option
- RFC 858 Telnet suppress go ahead option
- RFC 1091 Telnet terminal-type option
- RFC 1350 Trivial File Transfer Protocol (TFTP)
- RFC 1985 SMTP service extension
- RFC 2049 MIME
- RFC 2131 DHCP
- RFC 2132 DHCP options and BootP vendor extensions
- RFC 2554 SMTP service extension for authentication
- RFC 2616 Hypertext Transfer Protocol - HTTP/1.1
- RFC 2821 Simple Mail Transfer Protocol (SMTP)
- RFC 2822 Internet message format
- RFC 4330 Simple Network Time Protocol (SNTP) version 4
- RFC 5905 Network Time Protocol (NTP) version 4

VLAN support

- IEEE 802.1Q Virtual LAN (VLAN) bridges
- IEEE 802.1v VLAN classification by protocol and port
- IEEE 802.3ac VLAN tagging

Voice over IP (VoIP)

- LLDP-MED ANSI/TIA-1057
- Voice VLAN

Ordering Information**GS900MX and GS900MPX Series****AT-GS924MX-xx**

24-port 10/100/1000T stackable switch with
2 combo ports (10/100/1000T or 100/1000X SFP)
and 2 SFP+ stacking/user ports

AT-GS924MPX-xx

24-port 10/100/1000T PoE+ stackable switch with
2 combo ports (10/100/1000T or 100/1000X SFP)
and 2 SFP+ stacking/user ports

AT-GS948MX-xx

48-port 10/100/1000T stackable switch with
2 combo ports (10/100/1000T or 100/1000X SFP)
and 2 SFP+ stacking/user ports

AT-GS948MPX-xx

48-port 10/100/1000T PoE+ stackable switch with
2 combo ports (10/100/1000T or 100/1000X SFP)
and 2 SFP+ stacking/user ports

Where xx =

- 10 for US power cord
- 40 for Australian power cord
- 20 for no power cord
- 50 for European power cord
- 30 for UK power cord

Small Form Pluggable Optics Modules**1000Mbps SFP Modules**

1G SFP speed on 10G port is not supported.

AT-SPTX

1000T 100 m copper

AT-SPSX

1000SX GbE multi-mode 850 nm fiber up to 550 m

AT-SPEX

1000X GbE multi-mode 1310 nm fiber up to 2 km

AT-SPLX10

1000LX GbE single-mode 1310 nm fiber up to 10 km

AT-SPLX10/I

1000LX GbE single-mode 1310 nm fiber up to 10 km
industrial temperature

AT-SPBD10-I3

1000LX GbE Bi-Di (1310 nm Tx, 1490 nm Rx) fiber
up to 10 km

AT-SPBD10-I4

1000LX GbE Bi-Di (1490 nm Tx, 1310 nm Rx) fiber
up to 10 km

AT-SPLX40

1000LX GbE single-mode 1310 nm fiber up to 40 km

AT-SPZX80

1000ZX GbE single-mode 1550 nm fiber up to 80 km

100Mbps SFP Modules**AT-SPFX/2**

100FX multi-mode 1310 nm fiber up to 2 km

AT-SPFX/15

100FX single-mode 1310 nm fiber up to 15 km

AT-SPFXBD-LC-I3

100BX Bi-Di (1310 nm Tx, 1550 nm Rx) fiber up to 10 km

AT-SPFXBD-LC-I5

100BX Bi-Di (1550 nm Tx, 1310nm Rx) fiber up to
10 km

10GbE SFP+ Modules**AT-SPIOSR**

10GSR 850 nm short-haul, 300 m with MMF

AT-SPIOSR/I

10GSR 850 nm short-haul, 300 m with MMF
industrial temperature

AT-SPIOLRM

10GLRM 1310 nm short-haul, 220 m with MMF

AT-SPIOLR

10GLR 1310 nm medium-haul, 10 km with SMF

AT-SPIOLR/I

10GLR 1310 nm medium-haul, 10 km with SMF
industrial temperature

AT-SPIOLR20/I

10GER 1310 nm long-haul, 20 km with SMF
industrial temperature

AT-SP10ER40/I

10GER 1310 nm long-haul, 40 km with SMF
industrial temperature

AT-SP10ZR80/I

10GER 1550 nm long-haul, 80 km with SMF
industrial temperature

AT-SPIOTWI

1 meter SFP+ direct attach cable, AT-SP10TW1 can
also be used for hardware stacking

AT-SPIOTW3

3 meter SFP+ direct attach cable

AT-SPIOTW7

7 meter SFP+ direct attach cable



the solution : the network

Americas Headquarters | 19800 North Creek Parkway | Suite 100 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

EMEA & CSA Operations | Incheonweg 7 | I437 EK Rozenburg | The Netherlands | T: +31 20 7950020 | F: +31 20 7950021

alliedtelesis.com

© 2015 Allied Telesis, Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners.
617-000541 Rev. E