DIGITUS®

External SSD Enclosure, M2 - USB 3.0

Quick Installation Guide
DA-71111

Description

The aluminum enclosure enables the installation of a NGFF SSD which can be connected via USB to the PC or laptop.

Specification

- **Connector:**
  External: 1 x Micro USB 3.0 Type-B female
  Internal: 1 x NGFF 6 Gb/s slot
- **Chipset:** Asmedia ASM1153E
- Support UASP
- Support M.2 SATA SSD only, not support M.2 PCIE SSD
- Support SSD: 22x 30mm/42mm/60mm/80mm NGFF(M.2)
- Support Max. capacity of SSD to 512G
- Data transfer rate up to 5 Gb/s
- LED indicator for power and access
- **Color:** black
- Powered by USB3.0 cable, no extra power supply adapter needed
- Hot Plug, Plug & Play
- Assembled by screws

System requirements

Windows Vista/7/8/8.1/10.
Mac OS 10.8
Linux Kernel 2.6
PC or laptop with a free USB Type-A port

Package content

- External SSD Enclosure, M2 - USB 3.0
- Screwdriver, screws
- USB 3.0 Type-A to Micro USB cable (ca. 20 cm)

Hereby ASSMANN Electronic GmbH, declares that this device is in compliance with the requirements of Directive 2014/30/EU and the Directive 2011/65/EU for RoHS compliance. The complete declaration of conformity can be requested by post under the below mentioned manufacturer address.
Warning:
This device is a class B product. This equipment may cause some radio interference in living environment. In this case, the user can be requested to undertake appropriate measures to prevent interference.

www.assmann.com
Assmann Electronic GmbH
Auf dem Schüffel 3
58513 Lüdenscheid
Germany