

VE849

Multicast HDMI Wireless Extender

● The VE849 Multicast HDMI Wireless Extender extends your HDMI display up to 30m* from the HDMI source to up to four separate receivers, wirelessly. Easily connect two HDMI source devices, a local HDTV and up to four receivers (connected to HDTVs) wirelessly with crystal clear image quality capable of streaming Full 1080p with 5.1 channel Dolby digital audio and 3D technology. The IR remote control allows you to switch between HDMI source devices remotely from the receiver side and allows you to watch one local and four wirelessly connected HDTVs simultaneously.


Consisting of a wireless HDMI transmitter and receiver, the VE849 allows you to consolidate your HDMI devices. The VE849 can be used as:

- A wireless 2-port HDMI switch to connect remote devices (such as Blu-ray and media players) and complete your own wireless home cinema.
- An ideal addition to meeting rooms, allowing you to share presentations and video conferences to up to four different locations up to 30m* away.
- A part of your digital signage architecture, broadcasting ads or promotional videos wirelessly across a show room, boutique, or car dealership.



- Connect 2 HDMI inputs to 5 HDMI outputs (1 local + 4 remote) via wireless extension*
- Wirelessly extend four HDMI displays up to 30m* from the HDMI source
- Connect and transmit wireless video content from your Blu-ray DVD player, media players, or other HDMI device wirelessly
- Multicast signal 1 transmitter streams HDMI transmissions to 4 receivers simultaneously
- Supports Dynamic Frequency Selection (DFS) greatly reduces Wi-Fi signal interference for improved transmission quality and stability
- Wireless 3D supported
- Wireless Full HD (1080p) and 5.1 channel Dolby with AC3 and DTS digital audio
- Superior video quality: 480p, 720p, 1080i, and 1080p (24 / 30 / 60fps)
- Keeps home theater electronic devices neatly out-of-sight
- Built-in IR receiver with IR blaster cable allows control of remote source devices
- WHDI™ Technology Low latency <1ms
- HDCP compatible
- No software or driver installation needed
- * Distance may vary depending on the actual environment; solid objects such as steel, concrete, or brick may cause interference and shorten the transmission distance.





Wireless Home **Entertainment**

Specifications

	Function	VE849T	VE849R
Video Input	Interface	2 x HDMI Type A Female (Black)	N/A
	Impedance	100 Ώ	N/A
	Max Distance	1.8 m	N/A
Video Output	Interface	1 x HDMI Type A Female (Black)	1 x HDMI Type A Female (Black)
	Impedance	100 Ω	100 Ώ
Video	Max Data Rate	6.75 Gbps (2.25 Gbps Per Lane)	6.75 Gbps (2.25 Gbps Per Lane)
	Max Pixel Clock	225 MHz	225 MHz
	Compliance	HDMI (3D) HDCP compatible	HDMI (3D) HDCP compatible
	Max Resolutions / Distance	Up to 1080p@30m	Up to 1080p@30m
Audio	Input	2 x HDMI Type A Female (Black)	N/A
	Output	1 x HDMI Type A Female (Black)	1 x HDMI Type A Female (Black)
Control	IR	1 x 2.5mm Mini Stereo Jack Female (Black)	1 x 2.5mm Mini Stereo Jack Female (Black)
Power	Connector	1 x DC Jack	1 x DC Jack (Mini USB)
	Consumption	5 VDC, 10W	5 VDC, 7.5W (Mini USB)
Environment	Operating Temp.	0–40 °C	0–40 °C
	Storage Temp.	-20–60 °C	-20–60 °C
	Humidity	0–80% RH, Non-condensing	0–80% RH, Non-condensing
Physical Properties	Housing	Plastic	Plastic
	Weight	0.21 kg	0.13 kg
	Dimensions (L x W x H)	18.20 x 9.65 x 3.15 cm	9.50 x 9.50 x 3.15 cm

ATEN International Co., Ltd.

Printed 10/2015 V2.0

www.aten.com E-mail: marketing@aten.com

