

24 Port Cat6 UTP Patch Panel

BN-PP-624U

APPLICATION:

Category 6, Category 5e Patch Panel are based on 19" frame dimensions and have 24 modular jack RJ45 ports on 1RU. The Category 6, Category 5e Patch Panel will support the following applications, such as:

- Ethernet 10BASE-T, 100BASE-T (Fast Ethernet), 1000BASE-T (Gigabit Ethernet), 10GBASE-T
- 155 Mbps ATM, 622 Mbps ATM, 1.2 Gb/s ATM.
- Token ring 4/16.
- Digital video and broadband/baseband analog video.
- Voice over Internet Protocol (VoIP).
- Power-Over-Ethernet (PoE, PoE+).
- TP-PMD.
- ISDN.



Transmission Standard	ANSI/TIA-568-C.2 ISO/IEC 11801
Total Ports, quantity	24
Color	Black
Label	Write-on label, easy to identify
Package Quantity	1
Packaging Type	Bag
Rack Type	EIA 19 in Rack Units 1.0

24 Port Cat6 UTP Patch Panel BN-PP-624U

beek

Mechanical Specification

Panel Style	Straight
Material Type	High-impact, flame retardant, thermoplastic Steel
Panel Mounting	Flush
Metal Cable Management	Optional
Termination Type	IDC Wiring T568A T568B
Conductor termination range	22 AWG - 26 AWG
Conductor type	Solid or Stranded
Jack Termination Durability	>750 times
IDC Termination Durability	>250 times
Dust Cover	Yes

Electrical Specification

Contact Resistance	20 MΩ
Current Rating	1,5 Amps
DC Resistance	Max. 0,1Ω