

2M / 3M / 5M / 10M / 15M / 20M / 30M VGA Cable with 3.5mm Stereo Audio

2L-2502A/2L-2503A/2L-2505A/2L-2510A/2L-2515A/2L-2520A/2L-2530A

- The VGA Cable is designed to provide a high quality VGA with audio connection, ideally suited for high resolution applications up to 1920 x 1200. This durably constructed VGA cable with 3.5mm stereo audio eliminates the picture ghosting and fuzzy images, guaranteeing users the ultimate AV experiences.



Features

- Optimized for VGA with stereo audio transmission
- HDB15 male input and output
- Outer shielded material: Al Mylar tape
- A range of cable lengths, available from 2 to 30 m
- Compatible with ATEN VGA products

Specifications

Function	2L-2502A	2L-2503A	2L-2505A	2L-2510A	2L-2515A	2L-2520A	2L-2530A
Audio							
Input	3.5mm Stereo Audio Cable - Male (300 ± 10 mm) 3.5mm Stereo Audio Cable - Male (300 ± 10 mm)						
Conductor							
Material	Tinned Copper						
Conductor Diameter	30 AWG						
Jacketed							
Material	Jacket: PVC Shielding: AL-Mylar						
Connectors							
Video	HDB-15 Male HDB-15 Male						
Cable Length	2 m	3 m	5 m	10 m	15 m	20 m	30 m

Product information is subject to change without prior notice.

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com

Publish Date: 03/2019 V1.0



© Copyright 2019 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.