

CAT6 UTP 23AWG 4PAIR LSZH




STANDARDS

ANSI/TIA-568-C.2 IEC 61156-5
EN 50288-5-1
EN 50173
ISO/IEC 11801
EN 50575
EN 13501-6

APPLICATIONS

10BASE-T (IEEE 802.3)
4/16 Mbps TOKEN RING (IEEE 802.5)
100BASE-VG-AnyLAN
100 Mbps TP-PMD (ANSI X3T9.5)
100BASE-T (IEEE 802.3)
55/155 Mbps ATM
1000BASE-T (Gigabit Ethernet)
1.2 Gbps ATM



COLOR CODES

Insulation Color:
P1: White & Blue / Blue
P2: White & Orange / Orange
P3: White & Green / Green
P4: White & Brown / Brown
Jacket Color:
Option

CABLE PRINTING

Option

CONSTRUCTION

Conductor Material		Pure Solid Bare Copper
Conductor Number		8C(4 pairs)
Cable AWG		23
Construction($\pm 0.05\text{mm}$)		1/0.55
Separator		PE Cross
Rip Cord		Yes
Insulation	Material	PE
	Nom. Thickness(mm)	0.20
	Diameter($\pm 0.05\text{mm}$)	1.0
Jacket	Material	LSZH
	Nom. Thickness(mm)	0.50
	Diameter($\pm 0.30\text{mm}$)	6.30

ELECTRICAL PERFORMANCE

Max. Conductor DC Resistance (Ω/km)		93
Min. Insulation Resistance ($\Omega\text{M-KM}$)		500
Dielectric Strength		DC-1KV/1 Min
1.0-250MHZ Characteristic Impedance(ohms)		100 Ω $\pm$ 15 Ω
1.0-250MHZ Delay Skew(ns/100m)		≤ 45
Pair to Ground Capacitance Unbalance(Pf/100m)		≤ 330
Resistance Unbalance between pairs (%)		≤ 4
Max Mutual Capacitance		5.6nF/100m
Max DC Loop Resistance		19.2 Ω /100m
Before Aging	Tensile Strength(Mpa)	≥ 9
	Elongation(%)	≥ 100
After Aging 100°C*24h*7d	Tensile Strength(Mpa)	≥ 75
	Elongation(%)	≥ 50
Velocity of Propagation NVP		69%

PACKAGING

- 1.Easy Pull Box/ 305m
- 2.Reel/ 305m
- 3.Reel/ 500m

CAT6 UTP 23AWG 4PAIR LSZH


beek

C.2-568-TIA

Freq.	ATTN	RL	NEXT	ELFEXT	PS NEXT	PS ELFEXT
(MHz)	(dB/100m)	(dB)	(dB)	(dB/100m)	(dB/100m)	(dB/100m)
1	2.0	20.0	74.3	67.8	72.3	64.8
4	3.8	23.0	65.3	55.8	63.3	52.8
8	5.3	24.5	60.8	49.7	58.8	46.7
10	6.0	25.0	59.3	47.8	57.3	44.8
16	7.6	25.0	56.2	43.7	54.2	40.7
20	8.5	25.0	54.8	41.8	52.8	38.8
25	9.5	24.3	53.3	39.8	51.3	36.8
31.25	10.7	23.6	51.9	37.9	49.9	34.9
62.5	15.4	21.5	47.4	31.9	45.4	28.9
100	19.8	20.1	44.3	27.8	42.3	24.8
200	29.0	18.0	39.8	21.8	37.8	18.8
250	32.8	17.3	38.3	19.8	36.3	16.8

TIA Cat 6 Perm. Link

Wire Map	Res.	Length	Prop. Delay	Delay Skew	Freq.	Insertion Loss	NEXT	RL	ACR-N	ACR-F	PS NEXT	PS ACR-N	PS ACR-F
	Ω	Max.	nS	nS	MHz	dB	dB	dB	dB	dB	dB	dB	dB
12345678	i	90 m	498	44	1	3	65.0	19.1	62.0	64.2	62.0	59.0	61.2
12345678					4	3.5	64.1	21.0	60.6	52.1	61.8	58.3	49.1
					8	5	59.4	21.0	54.4	46.1	57.0	52.1	43.1
12345678S					10	5.5	57.8	21.0	52.3	44.2	55.5	49.9	41.2
12345678S					16	7	54.6	20.0	47.6	40.1	52.2	45.2	37.1
					20	7.9	53.1	19.5	45.2	38.2	50.7	42.8	35.2
					25	8.9	51.5	19.0	42.7	36.2	49.1	40.2	33.2
					31.25	10	50.0	18.5	40.0	34.3	47.5	37.6	31.3
					62.5	14.4	45.1	16.0	30.8	28.3	42.7	28.3	25.3
					100	18.6	41.8	14.0	23.3	24.2	39.3	20.7	21.2
					200	27.4	36.9	11.0	9.6	18.2	34.3	7.0	15.2
					250	31.1	35.3	10.0	4.2	16.2	32.7	1.6	13.2



ANKARA MERKEZ
İSTANBUL Malzeme Satış
İSTANBUL Network
İZMİR
BURSA

Tel: (312) 434 22 45 Faks: (312) 431 19 53
Tel: (212) 347 75 40 Faks: (212) 347 75 44
Tel: (216) 384 50 61 Faks: (216) 384 50 26
Tel: (232) 489 07 55 Faks: (232) 425 21 49
Tel: (224) 274 00 55 Faks: (224) 273 00 26
www.bimel.com.tr bimel@bimel.com.tr

bimel