



FO Pigtail set, 12 adet. LC, MM OM3 50/125 p loose buffer, Renk kodu DIN IEC 304,2m

Fiber optik Renkli pigtailler LC Simplex, SC Simplex ve ST simplex olarak önerilebilir.

Sınıfları OS2, OM1, OM2, OM3 and OM4 olabilir ve en üst performansı sağlar. Konnektörün

IEC 61754-4 2002 uyumluluğu vardır ve Zirkon Seramik halka yapıdadır. IEC 304 Renk kodlarına sahiptir.

(beyaz, mor, turkuaz, siyah, kırmızı, pembe, turuncu, gri, yeşil, sarı, kahverengi, mavi).

Geleceğe dönük standartlar ve yüksek kaliteli ağlar.

- LC simplex pigtail, OM3 50/125 u 2m
- Konnektörü IEC 61754-4-2002
- Çalışma sıcaklığı :-25°C... +80°C
- Depolama sıcaklığı :-20 °C... +65°C
- Kayıp değeri MM PC: maks. 0.4 dB
- Ger. kaybı MM PC: > 25 dB
- Zirkon seramik halka
- İkincil kaplama boyutları : $\varnothing 0.9 \pm 0.1$ mm
- ilk kaplama: arkalit : $\varnothing 250 \pm 15$ um
- Renkli tüpler, IEC 304 standardı beyaz, mor, turkuaz, siyah, kırmızı, pembe, turuncu, gri, yeşil, sarı, kahverengi, mavi
- 12 adet pakette
- Loose buffer tip

Pigtail



OM2

BC-FO-PT5ST-01

ST/UPC Fiber PigTail,
50/125 μ , multimode,
0.9mm simplex,
1 metre, Class OM2



OM2

BC-FO-PT5LC-01

LC/UPC Fiber PigTail,
50/125 μ , multimode,
0.9mm simplex,
1 metre, Class OM2



OM2

BC-FO-PT5SC-01

SC/PC Fiber PigTail,
50/125, multimode,
0.9mm simplex,
1 metre, Class OM2



OM3

BC-FO-PT5SC-01/3

SC/UPC Fiber PigTail,
50/125 μ , singlemode,
0.9mm simplex,
1 metre, Class OM3



OM3

BC-FO-PT5LC-01/3

LC/UPC Fiber PigTail,
50/125 μ , Multimode,
0.9mm Simplex,
OM3, LSZH, 1 metre



OM4

BC-FO-PT5SC-01/4

SC/UPC Fiber PigTail,
50/125 μ , Multimode,
0.9mm, Simplex,
OM4, LSZH, 1 metre



OM4

BC-FO-PT5LC-01/4

LC/UPC Fiber PigTail,
50/125 μ , Multimode,
0.9mm Simplex,
OM4, LSZH, 1 metre



OS2

BC-FO-PT9LC-01

LC/UPC Fiber PigTail,
9/125 μ , Singlemode,
0.9mm simplex,1 metr
Class OS2



OS2

BC-FO-PT9SC-01

SC/UPC Fiber PigTail,
9/125 μ , singlemode,
0.9mm simplex,
1 metre, Class OS2,
LSZH



OS2

BC-FO-PT9ST-01

ST/UPC Fiber PigTail,
9/125 μ , Singlemode,
0.9mm Simplex, OS2,
LSZH, 1 metre