

# FST-83A



## Core Alignment Fusion Splicer

FTTx Active Core Alignment Fusion Splicer

DACAS-Digital Analysis Core Alignment Systems

5' high resolution color LCD touch screen, 500X magnification, visible clearly with bare eyes

Packed with detachable 5200mAh battery, more than 250 times of splicing and heating

Auto-splicing mode, using friendly design

Integrated fiber-adjust frame performance is more stable

High-power 3 white LEDs simplifies your work at night

Detachable multifunction fixture, suitable for various fiber type

Dust-proof, water-proof, high-temperature resistance, adapting to various altitude and harsh environment


Fiber endface melter & fusion splicer 2 in 1



Integrated fiber-adjust frame



5' touch screen



Detachable multifunction fixture



**ECONOMIC  
FUNCTIONAL  
CONVENIENT  
RELIABLE**

Priority model FTTx and maintenance

# Splicer Master *FST-83A*

## Core Alignment Fusion Splicer

Tumtec provide the most professional optical fiber solution! Owing the strong self D&R team, combine domestic and foreign technologies, has become the renowned fusion splicer and fiber cleaver manufacture for more than 10 years.



### Standard Accessories

Fusion splicer FST-83A*1
Fiber cleaver*1
Battery*1
Power adapter*1
AC power line*1
Back-up electrode*1
Cooling tray*1
Carrying case*1
Carrying strap*1
User manual*1
Splicing test report*1
Miller stripper*1
Drop cable stripper*1
Alcohol bottle*1

### Equipment Parameters

Model	FST-83A
Dimension	136W*160L*148H (excluding rubber bumper) / 140W*165L*148H (including rubber bumper)
Weight	2280G (with battery) / 1900G (without battery)
Number of Fiber	Single
Applicable Fibers	SM(ITU-T G.652& G.657)/MM(ITU-T G.651)/DS(ITU-T G.653)/NZDS(ITU-T G.655)
Compatible Fiber/Cable	0.25 - 3.0mm/Indoor Cable
Cleaved Length	Diameter: 0.125 - 1 mm/Cleave Length: 8-16mm
Cladding Diameter	80 - 150 $\mu$ m
Splicing Mode	Pre-set 41 splicing modes, max 100 modes
Heating Mode	Pre-set 5 heating modes (20/30/40/50/60mm), max 100 modes
Typical Splice Loss	SM: 0.02dB / MM: 0.01dB/ DS: 0.04dB / NZDS: 0.04 dB/ G.657: 0.02dB (ITU-T Standard)
Return Loss	$\geq$ 60dB
Lighting	3 White LEDs
Splicing Time	Quick mode: 6s
Estimated Splice Loss	Available
Heating Sleeve Length	20 - 60 mm
Heating Time	Quick heating time: 13s, typical heating time: 30s
Results Storage	20000 latest records & 200 images
Tension Test	1.96 - 2.25N
Operating Condition	Operating Altitude: 0 - 5000m above sea level, 0 - 95% relative humidity, - 10 ~ 50 $^{\circ}$ C, Max Wind 15m/s
Storage Condition	0 ~ 95% relative humidity, -40 ~ 80 $^{\circ}$ C
Display	90 $^{\circ}$ bi-directional view, 5.0" Color High Resolution Display
Fiber View & Magnification	X, Y, XY, X/Y: 500X Magnification
Power Supply	AC Input 100 - 240V, DC Input 12 - 15V
No. of Splice/Heating with Battery	5200mAh Battery Capacity, Typical 250 times (Splice + Heat)
Operating Methods	Button/Touch Screen
Automatic Calibration	Automatic arc calibration by air pressure and temperature
Electrode Life	5000 arcs
Terminal	Mini USB 2.0

Tumtec reserve the right to change the design, properties and products without notice. ©2019 print in China



Foshan Tumtec Communication Technology Co., Ltd

Website: [www.gdtumtec.com](http://www.gdtumtec.com) Email: [enquiry@tumtec.com](mailto:enquiry@tumtec.com) Telephone: (+86)0757-63509010

Address: Rm 302-1, A5 building Hantian Hi-tech Zone, 17th Shenhai Road, Guicheng Avenue, Nanhai district, Foshan, Guangdong, China.