



5VDC 3A Multi-country Power Supply, 3.5/1.35mm

No.: 73824

Switching power supply for world wide use

Description

- Switching power supply with multi-country adapters for worldwide usage
- 5VDC 3A output for powering connected devices
- Standard DC jack for a simple connection
- UK, EU, US & AUS Adapters Included
- 2 Year Warranty

The Lindy multi-country power supply is a regulated and suitable solution for powering connected equipment which require an output voltage and amperage up to 5V 3A.

The included UK, EU, US & AUS adapters allow for global use of the power supply, while a standard DC jack ensures simple fitting with compatible devices.

Technical details

Specifications

- Input Voltage: 100...240VAC
- Input AC Frequency: 50...60Hz
- Output Voltage: 5V
- Output Voltage Accuracy: 4.75~5.25 V
- Output Current (max.): 3A
- Output Power: 15W
- Average active efficiency: 0.8139
- Efficiency at low load [10%]: Yes
- No-load Power Consumption: 0.1 W

Physical Properties

- Dimensions (approx.) WxDxH: 70x39x34mm [2.76x1.54x1.34in]
- DC Cable Length: 1.5m [4.92ft]
- DC Connector Size: 3.5/1.35mm
- Housing Material: Plastic
- Net Weight: 0.18kg [0.4lb]
- Operating Temperature: 0°C - 40°C [32°F - 104°F]
- Storage Temperature: -20°C - 70°C [-4°F - 158°F]
- Operating Humidity: 0 - 75% RH [non-condensing]
- Storage Humidity: 0 - 95% RH [non-condensing]
- Colour: Black

Miscellaneous

- Manufacturer Name: Powertron
- Commercial Registration No. : 91441900082613408
- Manufacturer Address: JinHe Indursty Area, Yufeng GuanLiQu,
ZhangMuTou, DongGuan City ,
523627
GuangDong China
- Manufacturer Model No.: PA1015-050IB300
- Packaging Type: Carton Box
- Packaging Dimensions: 120x90x60mm (4.72x3.54x2.36in)
- Gross Weight: 0.21kg (0.46lb)
- Warranty (Years): 2
- Certificated: EMC
LVD
ErP
UL
CCC
RCM
PSE
RoHS
REACH
California Proposition 65

Package Content

- Multi-country Power Supply
- UK, EU, US & AUS Adapters
- Lindy Manual

Purchasing Information

- No.: 73824
- EAN: 4002888738248