



2m Euro to C7 Mains Cable, lead free

No.: 30421

Euro Plug to IEC C7 Connector

Description

Euro Mains Plug to IEC C7 Cable for use in professional areas and private sectors
Provides max. 2.5A/250V to a device
Robust PVC housing and cable jacket, lead-free connectors (<0.1% lead in brass)
High temperature resistance allows the cable to be used in non air-conditioned areas
10 year warranty

Lindy Power Cables are high quality, reliable power delivery connections for use in a wide variety of professional and home environments.

This cable is perfect for the connection between small devices, such as beamers, DVD-players, small household devices and many more with IEC C8 port and the European electricity grid. The Euro connector works in many European countries.

The brass used in the connectors has a lead content of far below 0.1% and is therefore SVHC-free, as are all other materials used in these cables.

Please note that this cable is for use in dry areas only.

Euro Mains Plug to IEC C7 Mains Cables are available in the following lengths: 2m, 3m and 5m.

Technical details

Connectors

Connector A: Euro Plug CEEE 7/16

Connector B: IEC C7

Housing Material: PVC

Pin Construction:

A: Brass

B: Phosphor Bronze

Pin Plating: Nickel

Dimensions [approx.] WxDxH:

A: 35.5x45.5x13.7mm [1.4x1.79x0.54in]

B: 15.8x57x8mm [0.62x2.24x0.31in]

Cable Construction

Length: 2m [6.56ft]

Colour: Black

Conductor Material: Copper
Cable Material: H03VVH2-F 2x0.75mm²
Number of Wires: 2
Wire Gauge: 0.75mm²
Jacket Diameter: 5.5*3.5mm (0.22*0.14in)
Jacket Material: PVC

Specifications

Rated Voltage and Current: 2.5A/250V
Operating Temperature: -10°C - 60°C (14°F - 140°F)
Storage Temperature: -20°C - 70°C (-4°F - 158°F)

Miscellaneous

Packaging Type: Polybag
Warranty (Years): 10
Product Compliance: CE, RoHS, REACH, California Proposition 65

Purchasing Information

No.: 30421
EAN: 4002888304214

This product is also available in other lengths

30421 - 2m (6.56ft)
30422 - 3m (9.84ft)
30423 - 5m (16.40ft)