



## 2m Cat.6A S/FTP LSZH Network Cable, Grey

No.: 47604

RJ45, M/M, 500MHz, Copper

### Description

Twisted Pair Patch Cable with RJ45 connectors  
Cat.6A S/FTP PIMF, LSZH  
Integrated snagless connector for latch protection  
Gold plated pins for better conductivity and elimination of signal loss  
10 year warranty

Cat.6A S/FTP network cable with support for bandwidth up to 500MHz and features a snagless design with gold plated contacts for ethernet standards up to 10 GBase-T.

The Lindy Cat.6A Security Network Cable is a simple yet highly effective way of preventing accidental or malicious removal of cables on your network. Fully tamper resistant, Security key locks in the plug for added physical security allowing for removal only with the supplied key.

Cat.6A cable, shielded with braid as overall shield and foil shield for the individual wire pairs (S/FTP). Cat.6A cables meet the requirements of 10 Gigabit Ethernet (10GBaseT) with an operating frequency of up to 500MHz. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

The halogen-free sheath material of the LSZH cable makes the product suitable for use in public spaces with its low smoke emission and elimination of toxic halogen emissions.

Available lengths: 0.3m, 0.5m, 1m, 1.5m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m

### Technical details

#### Connectors

Connector A: RJ45 Male  
Connector B: RJ45 Male  
Housing Material: Polycarbonate  
Connector Plating: Nickel  
Pin Construction: Brass  
Pin Plating: Gold plated  
Dimensions [approx.] WxDxH: 11.6x21.5x8.3mm (0.46x0.85x0.33in)

**Cable Construction**

Length: 2m [6.56ft]  
Colour: Grey  
Type: Cat.6A  
Jacket Diameter: 6.0mm [0.24in]  
Jacket Material: LSZH  
Conductor Material: Copper  
Conductor Gauge: 26AWG  
Shielding: Aluminium Braid

**Specifications**

Supported Bandwidth: 500MHz  
Nominal Attenuation: 49.3dB/100m @ 500MHz  
Minimum Bend Radius: 72mm [2.84in]  
Operating Temperature: -10°C - 60°C [14F - 140°F]  
Storage Temperature: -10°C - 60°C [14F - 140°F]

**Miscellaneous**

Packaging Type: Polybag  
Warranty [Years]: 10  
Product Compliance: RoHS, REACH, UL

**Purchasing Information**

No.: 47604  
EAN: 4002888476041

**This product is also available in other lengths:**

47600 - 0.3m [0.98ft]  
47601 - 0.5m [1.64ft]  
47602 - 1m [3.28ft]  
47603 - 1.5m [4.92ft]  
47604 - 2m [6.56ft]  
47605 - 3m [9.84ft]  
47606 - 5m [16.44ft]  
47607 - 10m [32.81ft]  
47608 - 15m [49.21ft]  
47609 - 20m [65.62ft]