



EIZO S1911

19" LCD-Monitor

The S1911 is a high performance universal monitor for the professional user. The TN-panel with Overdrive ensures vivid colours and quick response times resulting in an outstanding image. With a resolution of 1280 x 1024, slim bezels, high contrast, brightness and with integrated speakers, the S1911 has features which make it an ideal choice for the trading room.

- Contrast 700:1, Brightness 300 cd/m², 170° Viewing Angles
- Automatic Brightness Stabilisation
- Integrated Speakers
- SlimEdge-Design with extremely narrow bezels
- DVI-D and D-Sub Inputs for Digital and Analogue connections



see what's next

EIZO S1911

Features

SlimEdge, smart and ergonomic Design

A modern LCD panel with extremely narrow side bezels of 12.8 mm around the screen area. Power pack and signal interface are optimally integrated into the equipment.

Outstanding image quality

A resolution of 1280 x 1024 pixels, contrast ratio of 700:1 and a brightness of 300 cd/m² result in sharp image quality. The LCD panel allows users a wide viewing angle and have a perfect view with an even contrast of colour and grey tones.

Precise Colour control

10 bit gamma correction automatically takes 8 bit input signals (256 tones for each primary colour) from the graphics board and uses a 10 bit Look-Up-Table (1,021 tones) to produce smoother, more accurate gradations of colour.

Colour Modes

This function offers three different colour modes with different pre-settings for brightness, colour temperature and gamma. On push of a button you receive ideal view conditions for applications of offices (text) and Internet (sRGB). A Custom mode for own preferences is also available. Over the provided software even an automatic change-over is possible, e.g. sRGB announcement with call of the Browsers.

Automatic Picture Adjustment

The screen has an automatic picture adjustment, which quickly and easily centres the picture on screen. At the same time the preferential brightness level is also automatically adjusted and kept constant.

Digital and Analogue Connectivity

A DVI-D and D-Sub inputs enable to connect 2 computers and allow automatic Signal synchronisation.

Audio

Speakers and headphone connections are smartly integrated at the rear of the cabinet.

Certifications



Note: With current LCD technology, a panel may contain a limited number of missing or flickering pixels

1. Average response time measured between each grayscale level of 31, 63, 95, 127, 159, 191, and 223.

Specifications

Panel Type	48 cm (19") TFT LCD
Available Cabinet Colours	Black or Grey
Active Display Size (HxV)	376 mm (Width) x 301 mm (Height)
Viewable Image Size	Diagonal: 481 mm
Native Resolution	1280 x 1024 pixels
Pixel Pitch	0.294 mm x 0.294 mm
Display Colours	16.77 Million
Max. Brightness	300 cd/m ²
Max. Contrast	700:1
Max. Viewing Angles	Horizontal: 170°; Vertical: 170°
On/Off Response Time	6 ms (typical)
Midtone Response Time ¹	2 ms (typical)
Features	Automatic picture area and position, On-Screen Display, PowerManager through VESA DPMS, Plug & Play, VESA DDC1/2B, Integrated power pack
Adjustment Features	Brightness, Clock, Phase, Picture position, Resolution, Gamma, Colour saturation for RGB and CMY, OSD-Language options (German, English, French, Spanish, Italian)
Resolutions	1280 x 1024 full picture 1:1, 1024 x 768, 800 x 600, 720 x 400 640 x 480, scalable
Horizontal frequency	24.8 – 80 kHz (Digital: 31 – 64 kHz)
Vertical frequency	50 – 75 Hz (Digital: 59 – 61 Hz)
Dot Clock	135 MHz (Digital: 108 MHz)
Input Signal	RGB Analogue, DVI standard 1.0
Input Terminals	DVI-D and DSub 15
Plug & Play	VESA DDC 2B
Power Save Settings	VESA DPMS, DVI-DMPM
Power Consumption	Max. 45 Watt, 1 Watt in Power Save Mode
Dimensions without Stand (WxHxD)	405 mm x 334 x 61 mm
Weight without Stand	5.2 kg
Certifications	CE, TÜV/GS, TÜV Ergonomics, ISO 13406-2, TCO'03, C-Tick, CB, UL, FCC-B, Canadian ICES-003-B, TÜV/S, VCCI-B, EPA ENERGY STAR, RoHS, WEEE, EIZO Eco Products 2006
Speakers	Left/Right
Audio	Dual 0.3 built-in speakers, input / headphone jacks
Accessories	Manual in German, English and French, Screenmanager Utility Disk., Mains, USB-, Audio- and Signal cable (DSub-DSub and DVI-D-DVI-D), ICC-Colour Profile
Warranty	5 Years (subject to conditions)
Height adjustable stand:	Vertical height adjustment of 100 mm, Tilt 30°, Swivel 35° left/right, Portrait and Landscape
Dimensions:	405 mm x (406 – 506 mm) x 205 mm
Weight:	7.2 kg

Stand Options

S1911SF-GY	Free mount in Grey
S1911SF-BK	Free mount in Black
S1911SH-GY	Height adjustable stand in Grey
S1911SH-BK	Height adjustable stand in Black

see what's next



Avnet Visual + Data Solutions:

Austria • +43 (0) 161 4880 • www.eizo.at

Belgium & Luxembourg • +32 (0) 2 709 9313 • www.eizo.be

Czech Republic • +420 283 851 997 • www.eizo.cz

Germany • +49 (0) 2153 733 400 • www.eizo.de

Hungary • +36 1 487 6161 • www.eizomonitor.hu

Italy • +39 02 660 851 • www.eizo.it

Netherlands • +31 (0) 40 265 9380 • www.eizo.nl

Slovakia • +421 (0) 254 773 980 • www.eizomonitor.sk

United Kingdom • +44 (0) 1483 719 500 • www.eizo.co.uk