



HDMI CABLES

Lindy HDMI cables are your go-to option for audio and video connections, ensuring crystal-clear transmission between various devices. With their robust construction, these cables are built to withstand demanding usage, delivering a seamless experience for high-definition content delivery. Whether in the world of professional audio visual setups or personal entertainment systems, Lindy HDMI cables provide reliable performance you can count on.

BLACK LINE HDMI CABLE



HDMI cable for home, and office applications and entry level high resolution solutions

Supports UHD 4K resolutions up to 4096x2160@60Hz

T		
T	0.5m	No. 36470
	1m	No. 36471
	2m	No. 36472
	3m	No. 36473
	5m	No. 36474
	7.5m	No. 36467
	10m	No. 36468
	15m	No. 36469

ANTHRA LINE HDMI CABLE



Professional choice HDMI cable for commercial and high performance AV and IT installations

Supports UHD 4K resolutions up to 4096x2160@60Hz

0.3m	No. 36960
0.5m	No. 36961
lm	No. 36962
2m	No. 36963
3m	No. 36964
5m	No. 36965
7.5m	No. 36966
10m	No. 36967
15m	No. 36968
20m	No. 36969

FIBRE OPTIC HYBRID HDMI 8K60 CABLE



Long distance HDMI solution

Hybrid design combines copper and fibre optic cable for reliable extended performance

Supports video resolutions up to UHD 8K 7680x4320@60Hz and 4K 4096x2160@120Hz

10m	No. 38510
15m	No. 38511
20m	No. 38512
30m	No. 38513
40m	No. 38514
50m	No. 38515
60m	No. 38516
70m	No. 38517
100m	No. 38518

ANTHRA LINE ULTRA HIGH SPEED HDMI CABLE



Professional choice Ultra High Speed HDMI cable for commercial and high performance AV and IT installations

Supports 10K resolutions up to 10240x4320 4:2:0 12bit

0.5m	No. 36951
lm	No. 36952
2m	No. 36953
3m	No. 36954

ACTIVE HDMI 4K60 CABLE





Creates a long distance HDMI connection between a 4K source device and display

Delivers reliable 4K@60Hz resolutions over longer cable distances

Active HDMI technology built into the connector for flexible installation

7.5m	No. 41016
10m	No. 41071
15m	No. 41072
20m	No. 41073
25m	No. 41074
30m	No. 41075



USB TYPE C CABLES

Experience the power of Lindy USB Type C cables, featuring robust construction and high-speed capabilities. These cables enable effortless information sharing and efficient technology integration, making them ideal for a wide range of AV applications.

Stay at the forefront of technology with Lindy's reliable and versatile Type C cables, ensuring a seamless AV experience in various settings.

3m ACTIVE USB 3.2 GEN 2 C/C CABLE

8K

3m USB 3.2 Gen 2 Active Cable for data and video extension Data transfer rates up to 10Gbps Supports DisplayPort 1.4 Alternate Mode Supports video resolutions up to UHD 8K 7680x4320@60Hz and 4K 4096x2160@120Hz

No. 43348

5m ACTIVE USB 3.2 GEN 2 C/C CABLE



5m USB 3.2 Gen 2 Active Cable for data and video extension

Data transfer rates up to 10Gbps

Supports DisplayPort 1.4 Alternate Mode

Supports video resolutions up to UHD 8K 7680x4320@60Hz and 4K 4096x2160@120Hz

No. 43308

10m USB 3.2 GEN 1 & DP 1.4 TYPE C HYBRID CABLE





10m USB 3.2 Gen 1 & DP 1.4 Type C Hybrid Cable for data and video extension Data transfer rates up to 5Gbps

Supports DisplayPort 1.4 Alternate Mode with video resolutions up to 4K 3840x2160@60Hz

Supports Power Delivery up to 60W (20V 3A)

No. 43333





DISPLAYPORT CABLES

Lindy DisplayPort cables are designed to support high bandwidth applications, making them suitable for applications requiring high data transfer rates, such as 4K and 8K video.

DisplayPort serves as a versatile and high-performance interface for transmitting audio and video signals between electronic devices and displays. This makes it ideal for a diverse array of applications, including gaming, digital signage, multi-monitor setups, and medical imaging.

ANTHRA LINE DISPLAYPORT 1.4 CABLE





Professional choice DisplayPort 1.4 cable for commercial and high performance AV and IT installations

Supports UHD resolutions up to 8K 7680x4320@60Hz 4:2:2 8bit including 4K 4096x2160@144Hz 4:2:2 10bit Robust ABS housing 24K gold plated connectors and contacts

0.5m	No. 36480
1m	No. 36481
2m	No. 36482
3m	No. 36483
5m	No. 36484

ACTIVE DISPLAYPORT 1.2 CABLE



Creates a long distance connection between a DisplayPort source device and display

Supports high quality resolutions up to 4K 60hz In-built active chipset for reliable longer length DisplayPort transmission

10m	No. 41078
15m	No. 41079
20m	No. 41081

FIBRE OPTIC HYBRID DP 2.0 UHBR10 CABLE

8K



Combines copper and fibre optic cable for a hybrid, long distance DisplayPort connectivity solution

Supports resolutions up to 4K@144Hz, 8K@60Hz

DP 2.0 standard with UHBR10 support, 40Gbps bandwidth (4 lanes, 10Gbps per channel)

10m	No. 38520
15m	No. 38521
20m	No. 38522
30m	No. 38523
40m	No. 38524
50m	No. 38525

FIBRE OPTIC HYBRID MINI DISPLAYPORT 1.4 CABLE WITH DETACHABLE DP CONNECTORS



Combines copper and fibre optic cable for a hybrid, long distance Mini DP & DP connectivity solution Supplied as a Mini DisplayPort Male to Male cable, with detachable DisplayPort connectors

Supports DP 1.4 resolutions up to 8K@60Hz, 4K@120Hz with additional support for static and dynamic HDR

10m	No. 38480
20m	No. 38481
30m	No. 38482
40m	No. 38483
50m	No. 38484
70m	No. 38485
100m	No. 38486



USB EXTENSION SYSTEM PRO

Surpass traditional USB distance constraints with the Lindy Active Extension System Pro. This innovative system utilises advanced repeater technology to extend USB signals seamlessly. Available in both USB 2.0 and USB 3.0/3.2 versions, these cables can function as standalone extensions or be daisy-chained to reach distances up to 60m for USB 2.0 and 40m for USB 3.0/3.2.

A variety of different configuration options are available. For a bespoke setup to meet your needs, please reach out to us and we'll be happy to suggest a customized solution just for you.

USB 3.0 A TO A ACTIVE EXTENSION SYSTEM PRO

Provides an extended connection between a computer and USB 3.0 device

Can be used standalone or daisy-chained to create bespoke extension systems of up to 40m USB A Male to A Female

	5Gbps
8m	No. 43158
10m	No. 43157
15m	No. 43229
20m	No. 43361

 20m
 No. 43361

 30m
 No. 43362

 10m with 4 Port Hub
 No. 43159

USB 2.0 A TO A ACTIVE EXTENSION SYSTEM PRO



Provides an extended connection between a computer and USB 2.0 device

Can be used standalone or daisy-chained to create bespoke extension systems of up to 60m USB A Male to A Female

480Mbps

8m	No. 42780
12m	No. 42782
30m	No. 42923
8m with 4 Port Hub	No. 42781
12m with 4 Port Hub	No. 42783

USB 3.2 GEN 1 C TO A ACTIVE EXTENSION SYSTEM PRO



Provides an extended connection between a USB Type C equipped computer and a USB Type A device

Can be used standalone or as part of the Lindy Active Extension System Pro (see above) to create bespoke extension systems of up to 40m USB Type C Male to A Female

	5Gbps
5m	No. 43380
8m	No. 43381

NEED TO EXTEND MULTIPLE USB DEVICES?



Use the 4 Port Hub Extensions to provide extended reach to multiple USB devices. 8m and 12m USB 2.0, and 10m USB 3.0 versions are available. See the tables above.

USB 3.2 GEN 1 A TO C ACTIVE EXTENSION



Can be used as a single extension or is compatible with the USB 3.0 Extension System Pro when used as the last segment in a daisy chain USB Type A Male to Type C Female

5Gbps



USB 2.0 & USB 3.0 ACTIVE EXTENSIONS

Effortlessly extend between a PC and USB devices. Choose USB 2.0 variants for swift 480Mbps transfers or increase speed with USB 3.0 boasting a rapid 5Gbps. Each cable features USB Type A Male to Type A Female connectors.

5m USB 2.0 SLIM ACTIVE EXTENSION



Supports transfer rates up to 480Mbps Chain up to 5 cables for a 25m reach Slim design eliminating the need for bulky plugs USB Type A Male to Type A Female



No. 42817

20m USB 2.0 ACTIVE EXTENSION



Supports transfer rates up to 480Mbps Chain 2 cables for a 40m reach USB Type A Male to Type A Female

480Mbps

No. 42631



5m USB 3.0 ACTIVE EXTENSION

Supports transfer rates up to 5Gbps

For even greater distances simply connect 2 cables in series

USB Type A Male to Type A Female



No. 43155

10m / 15m USB 3.0 ACTIVE EXTENSION



10m and 15m versions Chain 2 of the same cables together (to reach 20m or 30m) Supports an external power supply (not included) for use with high power devices USB Type A Male to Type A Female

5Gbps

10m No. 43156 15m No. 43099

3m / 15m USB 3.0 SLIM ACTIVE EXTENSION



3m and 15m versions Slimmer design eliminating the need for bulkier plugs Supports transfer rates up to 5Gbps

For longer reach, chain cables together (up to 4 cables for the 3m version; 2 cables for the 15m version) USB Type A Male to

Type A Female



3m	No. 43353
15m	No. 43322



50m USB 2.0 CAT.6 EXTENDER

Extends a USB 2.0 port up to 50m using low cost Cat. 5e/6 network cable (not included) Power over Cable requires a single power supply to be connected to the transmitter only Supports USB 2.0 High Speed and USB 1.1 Full Speed /

Low Speed

ROHS



50m 4 PORT USB 2.0 CAT.6 EXTENDER

Extends 4 USB 2.0 ports up to 50m using low cost Cat. 5e/6 network cable (not included)

Power over Cable requires a single power supply to be connected to the transmitter only

Supports USB 2.0 High Speed and USB 1.1 Full Speed / Low Speed



No. 42681

DIFFERENTIATE YOUR NETWORK WITH A HUGE RANGE OF COLOURS

ISO/ IEC 11801

Network cables discreetly facilitate data transmission and foster communication among a variety of devices, often operating in the background as the overlooked champions of our interconnected world.

Lindy Ethernet cables play a pivotal role in networking, audio-visual setups, and countless other applications.

Whether you're plugging in your computer to access the internet, or ensuring data flows seamlessly between servers in a data centre, patch cables are the dependable links that bridge the gap and keep our digital world running smoothly.

REACH

UL

COMPLIANT

WHY YOU NEED THEM

PROVIDES endless varieties. Lindy network cables are available in 9 different colours and lengths ranging from 0.3m to 30m

EQUIPPED with a connector designed to safeguard the latch and featuring gold-plated contacts

FEATURES S/FTP and U/UTP network cables that support bandwidths of up to 250MHz and 600MHz, respectively

ENSURES reliability with fully QC tested cables that are RoHS, REACH, and UL compliance certified, all supported by a 10-year warranty





DISPLAYPORT CONVERTERS

Lindy DisplayPort converters provide a versatile array of solutions to solve contemporary connectivity challenges, offering reliable options for seamless integration in both professional and consumer settings.

Specializing in AV signal conversion, Lindy ensures that electronic devices can effortlessly communicate and adapt to diverse connection requirements, facilitating a smoother and more efficient user experience.

DISPLAYPORT 1.2 TO HDMI 2.0 18G ACTIVE CONVERTER



Connects a DisplayPort computer to an HDMI 4K display

Supports resolutions up to 3840x2160@60Hz

Audio pass-through if supported by the video source

No. 41068

MINI DISPLAYPORT 1.2 TO HDMI 2.0 18G ACTIVE CONVERTER



Connects a Mini DisplayPort computer to an HDMI 4K display

Supports resolutions up to 3840x2160@60Hz

Audio pass-through if supported by the video source

No. 41069

No. 38145

DISPLAYPORT 1.4 TO HDMI 48G ACTIVE CONVERTER

8K



Connects a DisplayPort 1.4 computer to an HDMI 8K display

Supports resolutions up to 7680x4320@60Hz and 3840x2160 @120Hz Audio pass-through if

supported by the video source

No. 41094

DVI TO DISPLAYPORT ACTIVE CONVERTER

Converts DVI-D signals into DisplayPort

Supports resolutions up to 1920x1200@60Hz

Add a DisplayPort monitor as a secondary display

USB TYPE-C TO VGA CONVERTER



Converts a USB Type C port to a VGA port

Supports VGA resolutions up to 1920x1200@60Hz

Requires DisplayPort Alternate Mode support by the USB Port/Bus



No. 43355



USB TYPE C TO **HDMI 4K60 CONVERTER**



Converts a USB Type C port Supports HDMI resolutions up to 4K 3840x2160@60Hz Requires DisplayPort Alternate Mode support by

USB TYPE C TO DISPLAYPORT 8K60 CONVERTER



Converts a USB Type C port to an 8K capable DisplayPort connection

Supports resolutions up to 7680x4320@60Hz and 3840x2160@120Hz

Requires DisplayPort 1.4 Alternate Mode support by the USB Port/Bus

No. 43337

USB TYPE C TO HDMI 8K60 CONVERTER



Converts a USB Type C port to an 8K capable HDMI connection

Supports HDMI resolutions up to 7680x4320@60Hz and 3840x2160@120Hz Requires DisplayPort 1.4 Alternate Mode support by the USB Port/Bus

No. 43327

HDMI 4K60 TO DISPLAYPORT 1.2 CONVERTER



Connects an HDMI source to a DP display Supports resolutions up to 4K UHD 3840x2160@60Hz Includes USB cable for power supply

No. 38327

LOCK. CONNECT. PROTECT.

With easy plug-and-play installation, Lindy Cat.6A Locking Network Cables provide a comprehensive solution for those seeking both convenience and uncompromised security in their network connections.

Available In Lengths From 0.3m To 20m

CONTACT US FOR THE FULL RANGE





DOCKING STATIONS

Elevate your audio-video setups with Lindy docking stations, designed to optimize your AV workflow. Lindy docking stations offer unparalleled convenience, optimizing the connection of cameras, monitors, microphones, and other AV equipment.

Streamline your workflow, simplify your connections, and unlock the full potential of your AV setups with Lindy.

DST-PRO USB4

USB4 TYPE-C PC CONNECTION, SINGLE (8K) OR DUAL (4K) DISPLAY, 1X HDMI, 1X DP, 100W PASS-THROUGH CHARGING, BC 1.2

Supports 8K 30Hz for a single display or 4K 60Hz for two displays (Using DP MST)

Integrated 4 port USB 3.2 10Gbps Hub

3x USB 3.2 Type A, 1x Type C (data); 3x USB 2.0 Type A, 1x Type C (PD 3.0, 100W 20V 5A), RJ-45, Micro-SD & SD Card Reader, Audio



DST-PRO 5K XT **USB-C WITH TRIPLE DISPLAY (4K)** OR SINGLE DISPLAY (5K), HDMI & 2x DP, 100W PASS-THROUGH CHARGING, BC 1.2

Supports 5K@60Hz (DisplayPort) and 4K@60Hz (HDMI) for single and dual display options

Supports 1x 4K@60Hz & 2x 4K@30Hz for triple displays

USB 3.2 5Gbps support

3x USB Type A, 1 x USB-C (Data), 1x USB-C (Power Delivery + Data), RJ-45, Micro-SD & SD Card Reader, Audio



DST-PRO UNIVERSAL

USB-C & TYPE A UNIVERSAL CONNECTION WITH TRIPLE DISPLAY (4K), 3x HDMI, 2x DP, 100W PASS-**THROUGH CHARGING, BC 1.2**

Supports 4K@60Hz for single display option Supports 1x 4K@30Hz & 2x 4K@60Hz for triple displays 3x HDMI ports and 2x DP display connections

USB 3.2 10Gbps support

2x USB Type A, 1 x USB-C (Data), 1x USB-C (Power Delivery + Data), RJ-45, Audio



2 PORT KVM SWITCH DOCKING STATION COMBINES A KVM SWITCH & DOCKING STATION, CONTROL 2 DEVICES FROM A DUAL DISPLAY KVM CONSOLE, SINGLE (4K) OR DUAL (4K30 + 1080P) DISPLAY, BC 1.2





SPLITTERS & SWITCHES

In the current dynamic and highly competitive environment, delivering multimedia content effectively is paramount. Lindy Video Switches and Splitters are the essential tools behind this transformation.

These devices enable seamless sharing of screens and resources, making them ideal for collaborative meetings and presentations.

2 PORT HDMI 10.2G SPLITTER

Connects and splits a single HDMI source across two 4K displays

Supports resolutions up to 4K@60Hz 4:2:0 EDID Management for enhanced compatibility Compact design



No. 38158

4 PORT HDMI 18G SPLITTER

Splits a single HDMI 2.0 source across 4 HDMI displays Supports resolutions up to 4K@60Hz 4:4:4, with additional support for HDR HDCP 2.2 support for enhanced compatibility



No. 38236

2 PORT HDMI 8K60 SWITCH

Switches between 2 HDMI source devices when connected to a single display Supports 48G resolutions up to 8K@60Hz, with additional support for HDR Flexible control via push button, IR remote



No. 38337

4 PORT HDMI 18G SWITCH WITH AUDIO

Switches between 4 HDMI 2.0 source devices connected to a single HDMI 2.0 display

Supports resolutions up to 4K 60Hz, with additional support for HDR $\,$

Extracts digital and analogue audio from the HDMI source device



No. 38249

HDMI 4 PORT MULTI-VIEW SWITCH

Integrates 4 Full HD 1080p signals for display on a single HDMI display

Supports 4 viewing modes; Quad View, Picture & Picture, Dual Video and Standard

Seamless switching between inputs/viewing modes Independent switching of audio and video signals





HDMI MATRIX

Lindy Matrix systems ensure reliable performance, flexibility, and ease of use, setting a new standard in audio-visual connectivity. Ideal for control room and digital signage applications.

Explore the possibilities of intelligent AV signal routing with Lindy Matrix solutions.

4X4 HDMI 4K60 MATRIX

Connects up to four 4K source devices to four 4K displays or projectors in any combination Supports video resolutions up to 4K@60Hz 4:4:4 8bit Push buttons, IR remote and RS-232 for simple, flexible control



No. 38152

4X4 HDMI 4K60 MATRIX WITH VIDEO WALL SCALING

Switches between 4 HDMI source devices and 4 HDMI displays as a professional matrix

Creates classic video walls (up to 2x2) or vertical video walls (4x1) $\ensuremath{\mathsf{a}}\xspace$

Seamlessly switches between devices under 0.1ms



No. 38238

8X8 HDMI 18G MATRIX WITH VIDEO WALL SCALING

Switches between 8 HDMI source devices and 8 HDMI displays as a professional matrix

Creates single video walls (up to $4x^2$) or multiple video walls ($2x^2$)

Seamlessly switches between devices under 0.1ms



8X8 HDMI 4K60 MATRIX

Switches between 8 HDMI source devices and 8 HDMI displays connected simultaneously

Supports resolutions up to 4K 60Hz, with additional support for HDR $\,$

Allows for flexible and convenient switching between 8 HDMI sources, perfect for commercial and professional settings



No. 38334



HDBaseT EXTENDERS

No more hassles with multiple cables – Lindy HDBaseT solutions streamline your setup by allowing you to transmit stunning 4K video, audio, data, control and power - all through a single, cost-effective Cat 5e/6 cable.

Whether you're a home entertainment enthusiast, a business professional, or an AV integrator, Lindy HDBaseT technology offers unmatched versatility and performance.

70m HDBaseT PRESENTATION SYSTEM WITH CONTROL KEYPAD



Comprises a multi-AV transmitter, wall mounted control panel, and HDBaseT receiver wall plate

Supports resolutions up to 4K@30Hz 4:4:4

70m HDBaseT connection allows for a simple and flexible installation with PoH (Power over HDBaseT)

No. 38288





100m Extender System (Transmitter & Receiver)	No. 38340
100m Transmitter Module only	No. 38341
100m Receiver Module only	No. 38342



70m CAT.6 HDMI 4K60, IR & R-232 HDBaseT WALL PLATE TRANSMITTER

Neat wall plate HDBaseT transmitter that sends HDMI up to 70m Supports resolutions up to 4K@60Hz 4:4:4, HDR, RS-232, CEC, bi-directional IR PoC (Power over Cable) to power the remote receiver from the transmitter Can be used with the Lindy HDBaseT receiver module (No. 38214)



70m Wall Plate Transmitter 70m Receiver Module No. 38347 No. 38214





EXTENDERS

With a commitment to quality and performance, Lindy extenders empower users to create flexible and efficient AV setups, bridging the gap between sources and displays across extended distances with ease.

Explore the possibilities of extended connectivity with Lindy's comprehensive range of extenders.

50m CAT.6 HDMI 4K60 & IR EXTENDER WITH POC & LOOP OUT

 $\mathsf{Extends}\ \mathsf{4K}\ \mathsf{HDMI}\ \mathsf{18G}\ \mathsf{signals}\ \mathsf{over}\ \mathsf{50m}\ \mathsf{distances}\ \mathsf{with}\ \mathsf{standard}\ \mathsf{network}\ \mathsf{cable}$

Supports resolutions up to 3840x2160@60Hz 4:4:4 8bit, with support for HDR

An HDMI loop-through output creates an additional viewing zone with a local display



70m CAT.6 HDMI 4K30 & IR EXTENDER WITH POC & LOOP OUT

Extends HDMI & IR Signals up to 70m using a single Cat.6 Cable

Supports resolutions up to 3840x2160@30Hz 4:4:4 8bit Features a loop-through HDMI output on the Transmitter for local monitoring



300m FIBRE OPTIC HDMI 4K30 EXTENDER

Extends HDMI signals at distances of up to 300m using a single LC multimode mode fibre cable

Supports resolutions up to 3840x2160p@60Hz 4:2:0 8bit

10.2 Gbps Total Bandwidth over Single 2-core Fibre Optic Cable Link



300m/1000m FIBRE OPTIC HDMI 4K60, IR, RS232 & AUDIO EXTENDER

Extends HDMI 2.0 186 signals up to 300m over a simplex LC multimode cable or up to 1000m over a simplex LC singlemode cable Supports resolutions up to 4K 60Hz Ultra HD, with High Dynamic Range Bi-directional IR or RS-232 for seamless, flexible



SDV6E SYSTEM CONNECT. CONTROL. CREATE.

This advanced AV solution leverages the latest in SDVoE [Software Defined Video over Ethernet] technology to create and manage extended 4K60 AV distribution installations including control, matrix, video wall and multi view over a 10G Network with no latency.

The system consists of a Controller and Transceiver modules. Multiple Transceivers can function either as Encoders or Decoders for connecting to source or display devices. The Controller manages the entire installation via a web browser that supports signal preview and drag & drop operation.

The system can be used with both fibre and copper network connections and supports PoE for scalability and ease of installation. The Transceiver module can also be integrated into 3rd party SDVoE installations.





IPOWER SWITCH CLASSIC 8 REMOTE POWER MANAGEMENT FOR UP TO 8 DEVICES

LOCAL POWER. GLOBAL CONTROL.

The Lindy IPower Switch Classic 8 is the remote power management solution for seamlessly controlling the power status of 8 connected devices.

Control from anywhere in the world with your laptop and an internet connection! Now, system administrators can easily monitor and switch power to servers, workstations, hubs, routers and much more! The essential tool for remote troubleshooting and maintenance.

THE POWER TO PERFORM. ANYWHERE.



Power control of your devices from anywhere in the world with an internet connection



Reboot, switch on and off, monitor power consumption and status

IEC 320 C20 mains power input port

8x IEC C13 mains power output

13A/16A For use with a 13A or 16A circuit

- 2400W, 240V 10A per port
- Total switched power of 3120W