

TRB142 INDUSTRIAL RUGGED LTE RS232 GATEWAY

// TRB142 comes with a widely used RS232 interface for remote device management.



FLYER // TRB142

TRB142 360° VIEW



Copyright © 2024, TELTONIKA NETWORKS. Specifications and information given in this document are subject to change by TELTONIKA NETWORKS without prior notice.

TELTONIKA | Networks

KEY FEATURES

HARDWARE

Mobile	4G/LTE (Cat 1), 3G, 2G
CPU	Qualcomm, ARM Cortex A7, 1.2 GHz
Storage	512 MB Flash (200 MB for userspace)
Memory	128 MB RAM (50 MB for userspace)
Powering option	4-pin power socket, 9-30 VDC
SIM	1 x Internal SIM holder (2FF)
Antenna connectors	1 x SMA for mobile
Inputs/Outputs	On 4-pin socket: 2 x Digital input/Digital open collector output (configurable)
Serial	1 x RS232
Other	1 x Virtual network interface via micro USB
Status LEDs	3 x Connection type, 5 x Signal strength, 1 x Power
Operating temperature	-40° C to 75° C
Housing	Aluminium housing with DIN rail mounting option
Dimensions (W x H x D)	74.5 x 25 x 64.4 mm
Weight	135 g

SOFTWARE

RutOS
TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, FTP, SMTP, SSLv3, TLS 1.3, ARP, PPP, PPPoE, DHCP, Telnet
WEB UI, CLI, SSH, CALL, SMS, TR-069, SNMP, JSON-RPC, MQTT, MODBUS, RMS
Ping Reboot, Wget reboot, Periodic Reboot, LCP and ICMP for link inspection
RMS, FOTA, Azure IoT Hub, Cloud of Things, Cumulocity, ThingWorx
TCP client, TCP server, RTU server, RTU gateway, Modbus over MQTT
Console, Over IP, Modem, NTRIP, Modbus

