



P/N	L/ (mm)	T/ (mm)
BC-DSP-VG-MM-018-1	1800	30
BC-DSP-VG-MM-03-1	3000	40

NOTES:

1. Open/Short/Intermittence: 100%
2. Insulation Resistance: 10M Ω Min
3. Conductive Resistance: 5 Ω Max
4. Graphics Resolution: 1440*900@60Hz
5. RoHS & REACH COMPLIANT

PIN OUT

P1	P2
1	1
2	2
3	3
5	5
6	6
7	7
8	8
10	10
13	13
14	14
SHELL	DRAIN
	SHELL

⑤	FERRITE	∅14*28.5*∅9.0	2	PCS
④	MOLDED	45P BLACK PVC		G
③	MOLDED	LDPE		G
②	CONNECTOR	VGA 15P MALE, GOLD PLATED PIN, BLUE INSULATION, NICKEL PLATED SHELL	2	PCS
①	CABLE	(7/0.1BC*1C+FPE+D+AL+PVC)*3C+7/0.1BC*4C+ADB BLACK PVC JACKET, OD:8.0±0.2mm MARKING:AWM STYLE 2919 80℃ 30V LOW VOLTAGE COMPUTER CABLE ROHS COMPLIANT	L	MM
NO.	MATERIAL	DESCRIPTION	QTY.	UNIT

Ltemref	Quantity	Title/Name, designation, material, dimension etc			Article NO./Reference		
Designed by FLY		Checkde by HELEN	Approved by - date 2022. 12. 30	File name	Date 2022. 12. 30		Scale FREE
ANGLE: 				BC-DSP-VG-MM-0X-1			
UNIT:MM					Edition 1	Sheet 1/1	