



P/N	L/ (mm)	T/ (mm)
BC-DSP-VG-MM-30-1	30000	200

PIN OUT

P1	P2
1	1
2	2
3	3
5	5
6	6
7	7
8	8
10	10
13	13
14	14
SHELL	DRAIN
	SHELL

NOTES:

1. Open/Short/Intermittence: 100%
2. Insulation Resistance: 10MΩ Min
3. Conductive Resistance: 10Ω Max
4. Graphics Resolution: 1440*900@60Hz
5. RoHS & REACH COMPLIANT

NO.	MATERIAL	DESCRIPTION	QTY.	UNIT
⑤	FERRITE	∅14*28.5*∅9.0	2	PCS
④	MOLDED	45P BLACK PVC		G
③	MOLDED	LDPE		G
②	CONNECTOR	VGA 15P MALE, GOLD PLATED PIN, BLUE INSULATION, NICKEL PLATED SHELL	2	PCS
①	CABLE	(7/0.12BC*1C+FPE+D+AL+PVC)*3C+7/0.12BC*4C+ADB BLACK PVC JACKET, OD:8.0±0.2mm MARKING:AWM STYLE 2919 80°C 30V LOW VOLTAGE COMPUTER CABLE ROHS COMPLIANT	L	MM

Ltemref	Quantity	Title/Name, designation, material, dimension etc			Article NO./Reference	
Designed by FLY	Checkde by HELEN	Approved by - date 2022. 12. 30	File name	Date 2022. 12. 30	Scale FREE	
ANGLE:				BC-DSP-VG-MM-30-1		
UNIT:MM					Edition 1	Sheet 1/1