





NOTES:

1. Open/Short/Intermittence: 100%
2. Hi-Pot: AC 100V 0.01S 1mA
3. Insulation Resistance: DC 100V 0.01S 5MΩ Min
4. Conductive Resistance: 5Ω Max
5. X5 hard disk read and write speed test:
READ ≥ 800MB/S
WRITE ≥ 800MB/S
6. Support PD3.0 20V 5A protocol
7. RoHS & REACH COMPLIANT

PIN OUT



⑥	DUST CAP	TYPE C MALE DUST CAP	2	PCS
⑤	MOLDED	45P BLACK PVC		G
④	MOLDED	LDPE		G
③	CONNECTOR	USB3.2 TYPE C MALE, GOLD PLATED PIN, NICKEL PLATED SHELL+SHIELDING SHELL+HUSB332A	1	PCS
②	CONNECTOR	USB3.2 TYPE C MALE, GOLD PLATED PIN, NICKEL PLATED SHELL+SHIELDING SHELL	1	PCS
①	CABLE	(1/0. 2BC*1P+D+AM+HM)*4C+1/0. 2BC*1P+1/0. 20BC*4C+7/0. 20BC*2C+DAB, BLACK PVC JACKET, OD: 4. 5±0. 2MM MARKING: E***** 兄 AWM STYLE 2725 80℃ 30V VW-1 SUPER HIGH SPEED USB	L	MM
NO.	MATERIAL	DESCRIPTION	QTY.	UNIT

Item ref	Quantity	Title/Name, designation, material, dimension etc			Article NO. /Reference		
Designed by FLY	Checkde by HELEN	Approved by - date 2023. 01. 17	File name	Date 2023. 01. 17	Scale FREE		
ANGLE:				BC-USB-CMM-10G-01			
UNIT:MM						Edition 1	Sheet 1/1