

# MMA 120X / 240X

## 5 ZONE MIXING AMPLIFIERS

The MMA 120X and 240X are 120 W and 240 W rated Class-D mixing amplifiers engineered for multi-zone audio distribution in commercial or industrial environments. Each model includes five zone speaker outputs and supports both 100 V line and low-impedance connections. With one slot for a plug-in music source module, six Mic/Line inputs, a dedicated paging microphone input (compatible with the Page Station 5), phantom power, chime, priority input control, and a built-in graphic equalizer, the units are optimized for public address and background music broadcasting in up to five zones.



Technical Specifications	MMA 120X	MMA 240X
Output power (RMS)	120 W	240 W
Power supply	AC ~230 V, 50Hz	
Outputs	Low impedance output - 4 $\Omega$ (Phoenix connector) Hi impedance outputs - 100 V (Phoenix connector)	
Inputs	Microphone: sensitivity - 50 dBu, connectors - balanced XLR, 6.3mm TRS Jack Line: sensitivity - 30 dBu, connector - stereo RCA Remote mic: sensitivity - 40 dBu, connector - Phoenix Link in: sensitivity -17 dBu, connector - 6.3 mm TS Jack Amp in: sensitivity - 0 dBu, connectors - 6.3 mm TS Jack Remote paging: connector - RJ45	
Phantom power	15 V (max.)	
Frequency response	80 Hz -15 kHz	
THD	< 0,5 %	
Signal / noise ratio	75 dB	
Equalizer	125 Hz, 250 Hz, 500 Hz, 1 kHz, 2 kHz, 4 kHz, 8 kHz, $\pm$ 12 dB	
Optional accessories	Page station 5 - five zones paging microphone	
Dimensions	420 mm x 320 mm x 88 mm	
Weight	9.76 kg	10.5 kg

# MMA 120X / 240X

## 5 ZONE MIXING AMPLIFIERS

Front panel view



Rear panel view

