

OUTDOOR LTE/WI-FI ANTENNA FOR RUT2-SERIES ROUTERS

IP68

Water and dust-resistant for ultimate outdoor reliability

OMNIDIRECTIONAL

Designed for reliable signal coverage from every direction

INTEGRATED MOUNTING BRACKET

Quick and easy pole/mast mounting

PERFECT ROUTER MATCH

Compatible and designed to contain select Teltonika routers

The antenna is supplied without a router









TECHNICAL DATA

LTE ANTENNA

| Frequency Range | 617 ~ 960, 1700 ~ 2200, 2300 ~ 2700, 3300 ~ 3800 MHz |
|-----------------------|--|
| Polarisation | Vertical |
| Radiation pattern typ | oe Omnidirectional |
| Gain | Max 4 dBi |
| V.S.W.R | <2.00 |
| Impedance | 50 Ω |
| Connector type and | count 2x SMA male |

WI-FI ANTENNA

| Frequency Range | 2400 ~ 2500 MHz |
|--------------------------|-----------------|
| Polarisation | Vertical |
| Radiation pattern type | Omnidirectional |
| Gain | 6 dBi |
| V.S.W.R | <2.00 |
| Impedance | 50 Ω |
| Connector type and count | 1x RP-SMA male |

MECHANICAL/ENVIRONMENTAL

| Cable | 3x RG316 |
|-----------------------|---------------------|
| Operating Temperature | -40 °C to 75 °C |
| Mounting Method | Wall, ceiling, mast |
| IP rating | IP68 |
| Weight | 1500 g |
| RoHS compliant | V |



