



# AT-2801FX

## Fast Ethernet PCMCIA Fiber Adapter Card

### AT-2801FX/xx-001

100BaseFX 32-bit Ethernet adapter

### Mobile Connectivity Through Fiber

Allied Telesis' AT-2801FX PCMCIA card is designed to provide notebook computers with network connections through a high speed fiber-optic link via a 32-bit PCMCIA interface. The AT-2801FX card features an ST or SC fiber connection, supports the Microsoft Windows 2003 and XP operating systems, and is compliant with industry standards.

### Single Piece, Solid Enclosure for High Reliability

Allied Telesis' AT-2801FX comes with a variety of reliability features. The single-piece, integrated design of the AT-2801FX endures frequent usage with no damage to the fiber connectors, making the card a solid solution for military and government usage.

### Comprehensive Software Support

Allied Telesis' AT-2801FX adapter cards feature software to assist users with network setup and configurations. An offline user diagnostics program provides system administrators and engineers with a valuable tool to analyze the network adapter and check data. And finally, the AT-Setup program simplifies controlling and configuring all AT-2801FX adapters.

### Specifications

#### LED Status Indicators

Link	ON	100Mbit/s connection
	OFF	No connection
FDX	ON	Full-Duplex
	OFF	Half-Duplex

### PC Interface

PC card standard release 8.1 and 68 pin connector  
Network Connector  
Full-duplex or half-duplex mode  
100BaseFX ST or SC Fiber connector

### Driver Support

Windows 2K  
Windows XP  
Windows 2003

### Power Characteristics

+5V

### Environmental Specifications

Operating Temp. 0°C to 40°C  
Operating Humidity 5% to 90%

### Physical Characteristics

Dimensions 16 x 54 x 120 mm  
(H x W x D)  
Weight 0.1 lb

### Standards & Compliance

IEEE Std 802.3u Standard for Fast Ethernet  
IEEE Std 802.3x Standard for 802.3 full duplex operation

PC Card Standard Release 8.1  
PCMCIA Release 2.x

### Electrical/Mechanical Approvals

FCC/EN55022 Class B  
VCCI B  
TUV  
UL  
CSA  
CE  
C-Tick  
EN55024 (Immunity)

### Key Features

- 100Mbps Fiber port with SC or ST connector
- 32-bit PC Card w/68pin connector
- Half- or full-duplex operation
- Flow Control (802.3x)
- Advanced Power Management (ACPI)
- Support Wake-on-LAN (WOL) function and remote wake-up
- PCI 2.2 compliant
- Supports Microsoft Windows 2003 and XP
- RoHS Compliant

### Ordering Information

**AT-2801FX/xx-001**  
100BaseFX 32-bit Ethernet adapter

Where xx = ST for ST Fiber Connector  
= SC for SC Fiber Connector

USA Headquarters | 19800 North Creek Parkway | Suite 200 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895  
European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11  
Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

[www.alliedtelesis.com](http://www.alliedtelesis.com)