Brand-Rex Copper Connectivity - GigaPlus Jacks
Category 5e Snap-In-Jacks - Shielded and Unshielded

PRODUCT DESCRIPTION:

GigaPlus Shielded and Unshielded Snap-In-Jacks offer true Category 5e component performance. The jacks are backward compatible and also fully compatible with all our UK and Continental style faceplates and products. Each jack is supplied with a short form installation instruction and cable tie.

PRODUCT CHARACTERISTICS:

Outlet Style:	Shielded / Unshielded Keystone type with unkeyed RJ-45 ports
Cable Entry:	Top and Rear
Hole Plate Thickness:	1.60mm max
Body Material:	Impact modified PBT UL94 - V0 rated
Jack Contacts:	Phosphor Bronze
Plating:	50 µm gold over 100 µm nickel
Punch Down Blocks:	110 or LSA style IDC
IDC Contacts:	Phosphor Bronze
Wiring Standard:	EIA/TIA 568A/B
Conformance:	ISO/IEC 11801 : 2002 & Amm1 ANSI/TIA/EIA 568C EN50173-1 : 2007

Product Part Numbering

	Unshielded	Shielded
LSA Style - Black	GPCJAKU0K2	GPCJAKF0K2
LSA Style - White	GPCJAKU0K3	-
110 Style - Black	GPCJAKU012	GPCJAKF012
110 Style - White	GPCJAKU013	-

Other colours available on request.